



SAFETY DATA SHEET

Version #: 01
Issue date: 12-April-2023
Revision date: -
Supersedes date: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance	US Export Gasolines - All Grades (Refer to Synonyms for Product Name)
Identification number	649-378-00-4 (Index number)
Registration number	01-2119471335-39-0088
Synonyms	93 Oct Conventional * 87 Oct Conventional * 87 Oct Conventional 7.8 RVP * 87 Oct Conventional 9.0 RVP * 87 Oct Conventional 11.5 RVP * 87 Oct Conventional 13.5 RVP * 87 Oct Conventional 15.0 RVP * VOC Region 1 RBOB Prem for 10%EtOH Blend * VOC Region 2 RBOB Prem for 10%EtOH Blend * RBOB Prem 11.5 RVP for Blndg w/10.0%EtOH * RBOB Prem 13.5 RVP for Blndg w/10.0%EtOH * RBOB Prem 15.0 RVP for Blndg w/10.0%EtOH * VOC Region 1 RBOB Unl for 10%EtOH Blend * VOC Region 2 RBOB Unl for 10%EtOH Blend * RBOB Unl 11.5 RVP for Blndg w/10.0%EtOH * RBOB Unl 13.5 RVP for Blndg w/10.0%EtOH * RBOB Unl 15.0 RVP for Blndg w/10.0%EtOH * Unl Conv for Oxy Blndg 7.0RVP, Atlanta * Unl Conv for Oxy Blndg 7.8RVP, Atlanta * Unl Conv for Oxy Blndg 9.0RVP, Atlanta * Unl Conv for Oxy Blndg 11.5RVP, Atlanta * Unl Conv for Oxy Blndg 13.5RVP, Atlanta * Unleaded Conv Blndstk Oxy Blendg 7.8RVP * Unleaded Conv Blndstk Oxy Blendg 9.0RVP * Unleaded Conv Blndstk Oxy Blendg 11.5RVP * Unleaded Conv Blndstk Oxy Blendg 13.5RVP * Unleaded Conv Blndstk Oxy Blendg 15.0RVP * CBOB Unleaded
SDS number	2001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Distribution of a substance. Formulation and repackaging of substances and mixtures. Manufacture of substance. Use as a fuel. Use as intermediate.
Uses advised against	All other uses.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	Valero Energy (Ireland) Ltd 1st Floor, Block B
Address	D22 X0Y3, Quarryvale Ireland
Telephone	01/210 345 4593 (General information; US)
e-mail	CorpHSE@valero.com
Contact person	Industrial Hygienist

1.4. Emergency telephone number 0044/(0)18 65 407333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 1	H224 - Extremely flammable liquid and vapour.
-------------------	------------	---

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Germ cell mutagenicity	Category 1B	H340 - May cause genetic defects.
Carcinogenicity	Category 1B	H350 - May cause cancer.
Reproductive toxicity	Category 2	H361 - Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

Aspiration hazard

Category 1

H304 - May be fatal if swallowed and enters airways.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with long lasting effects.

2.2. Label elements**Label according to Regulation (EC) No. 1272/2008 as amended****Contains:** Gasoline ; Low boiling naphtha - unspecified**Hazard pictograms****Signal word**

Danger

Hazard statements

H224 Extremely flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H340 May cause genetic defects.
 H350 May cause cancer.
 H361 Suspected of damaging fertility or the unborn child.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P201 Obtain special instructions before use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
 P331 Do NOT induce vomiting.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal

Not assigned.

Supplemental information on the label

None.

2.3. Other hazards

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Hydrogen sulphide (H₂S) can accumulate in the headspace of storage tanks and reach potentially hazardous concentrations.

This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII. The substance is not included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties. The substance is not considered to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients**3.1. Substances****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Gasoline ; Low boiling naphtha - unspecified	90 - 100	86290-81-5 289-220-8	01-2119471335-39-0088	649-378-00-4	
Classification: Flam. Liq. 1;H224, Skin Irrit. 2;H315, Muta. 1B;H340, Carc. 1B;H350, Repr. 2;H361, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					

Additional components

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Toluene	5 - 20	108-88-3 203-625-9	-	601-021-00-3	#
Ethanol	0 - 10	64-17-5 200-578-6	-	603-002-00-5	

Additional components

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Benzene	0.1 - 1	71-43-2 200-753-7	-	601-020-00-8	#

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Composition comments This product is registered under the REACH Regulation 1907/2006 as a UVCB. All concentrations are in percent by weight unless ingredient is a gas.
The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

- 6.2. Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
- 6.3. Methods and material for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains.
- Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
- Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Absorb spillage with suitable absorbent material. Clean surface thoroughly to remove residual contamination.
- Never return spills to original containers for re-use. Put material in suitable, covered, labelled containers. The product is insoluble in water.
- 6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
- 7.2. Conditions for safe storage, including any incompatibilities** Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).
- Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended
- ANNEX 1, PART 1 Categories of dangerous substances
Hazard categories in accordance with Regulation (EC) No 1272/2008
- P5a FLAMMABLE LIQUIDS (Lower-tier requirements = 10 tonnes; Upper-tier requirements = 50 tonnes)
- E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tonnes; Upper-tier requirements = 500 tonnes)
- 7.3. Specific end use(s)** Observe industrial sector guidance on best practices. For detailed information, see section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ireland. Occupational Exposure Limits

Material	Type	Value
Gasoline ; Low boiling naphtha - unspecified (CAS 86290-81-5)	STEL	500 ppm
	TWA	300 ppm
Additional components	Type	Value
Benzene (CAS 71-43-2)	TWA	3.25 mg/m ³
		1 ppm
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
	TWA	100 ppm
		192 mg/m ³
		50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Additional components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m3
		100 ppm
	TWA	192 mg/m3
		50 ppm

EU. OELs, Directive 2004/37/EC on carcinogen and mutagens from Annex III, Part A

Additional components	Type	Value
Benzene (CAS 71-43-2)	TWA	3.25 mg/m3
		1 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)**General population**

Product	Value	Assessment factor	Notes
US Export Gasolines - All Grades (Refer to Synonyms for Product Name) (CAS 86290-81-5)			
Long-term, Local, Inhalation	178.57 mg/m3	10	
Short-term, Local, Inhalation	640 mg/m3	15	
Short-term, Systemic, Inhalation	1152 mg/m3	15	

Workers

Product	Value	Assessment factor	Notes
US Export Gasolines - All Grades (Refer to Synonyms for Product Name) (CAS 86290-81-5)			
Long-term, Local, Inhalation	837.5 mg/m3	6	
Short-term, Local, Inhalation	1066.67 mg/m3	9	
Short-term, Systemic, Inhalation	1286.4 mg/m3	9	

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines**Ireland Exposure Limit Values: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection should meet standard EN 166.

Skin protection

- Hand protection Wear suitable gloves tested to EN374. In full contact: Glove material: Nitrile rubber. Layer thickness: 0.225 mm. Breakthrough time: >480 min. Splash contact: Glove material: Neoprene; Layer thickness: 0.75 mm; Breakthrough time: 10-30 min.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P2) can be used.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	Colorless to yellow.
Odour	Petroleum.
Melting point/freezing point	Not determined.
Boiling point or initial boiling point and boiling range	> 25 - < 220 °C (> 77 - < 428 °F)
Flammability	Extremely flammable liquid and vapour.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	1.4
Explosive limit – upper (%)	7.6
Flash point	< -40 °C (< -40 °F) Tagliabue closed cup Cup ASTM D56
Auto-ignition temperature	> 280 °C (> 536 °F)
Decomposition temperature	Not determined.
pH	Not determined.
Kinematic viscosity	< 1 mm ² /s
Solubility	
Solubility (water)	Insoluble in water.
Partition coefficient (n-octanol/water) (log value)	> 2 - < 7
Vapour pressure	> 35 - < 90 kPa @ 37.8 °C (100 °F)
Density and/or relative density	
Density	Not determined.
Vapour density	> 3 - < 4 Typical.
Particle characteristics	Not applicable.

9.2. Other information

9.2.1. Information with regard to physical hazard classes No relevant additional information available.

9.2.2. Other safety characteristics

Viscosity ≤ 1 mm²/s @ 40 °C (104 °F)

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity May be fatal if swallowed and enters airways.

Product	Species	Test Results
Gasoline ; Low boiling naphtha - unspecified (CAS 86290-81-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
<i>Vapour</i>		
LC50	Rat	> 5610 mg/m ³ , 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	May cause genetic defects.	
Carcinogenicity	May cause cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Benzene (CAS 71-43-2)	1 Carcinogenic to humans.	
Gasoline ; Low boiling naphtha - unspecified (CAS 86290-81-5)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Mixture versus substance information	No information available.	

11.2. Information on other hazards

Endocrine disrupting properties	This substance does not have endocrine disrupting properties with respect to human health, as it does not meet the assessment criteria laid out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605.
Other information	Hydrogen sulphide, a highly toxic gas, may be present. Signs and symptoms of overexposure to hydrogen sulphide include respiratory and eye irritation, dizziness, nausea, coughing, a sensation of dryness and pain in the nose, and loss of consciousness. Odour does not provide a reliable indicator of the presence of hazardous levels in the atmosphere.

SECTION 12: Ecological information

12.1. Toxicity	Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.
12.2. Persistence and degradability	Expected to be inherently biodegradable.
12.3. Bioaccumulative potential	The product is not bioaccumulating.
Partition coefficient n-octanol/water (log Kow)	Gasoline ; Low boiling naphtha - unspecified (CAS 86290-81-5) 2 - 7
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	The product is insoluble in water.
12.5. Results of PBT and vPvB assessment	This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.
12.6. Endocrine disrupting properties	This substance does not have endocrine disrupting properties with respect to the environment, as it does not meet the assessment criteria laid out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605.
12.7. Other adverse effects	Oil spills are generally hazardous to the environment. The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1203
14.2. UN proper shipping name	GASOLINE
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
14.4. Packing group	II
14.5. Environmental hazards	Yes
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1203
14.2. UN proper shipping name	GASOLINE
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	Yes
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1203
14.2. UN proper shipping name	GASOLINE
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	Yes
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1203
14.2. UN proper shipping name	GASOLINE
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	II
14.5. Environmental hazards	Yes
ERG Code	3H

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

14.1. UN number UN1203

14.2. UN proper shipping name GASOLINE

14.3. Transport hazard class(es)

Class 3

Subsidiary risk -

14.4. Packing group II

14.5. Environmental hazards

Marine pollutant Yes

EmS F-E, S-E

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not applicable. However, this product is a liquid and if transported in bulk covered under MARPOL 73/78, Annex I.

General information Shipping descriptions in this section are offered as examples only. Classification for transport must accurately reflect the material hazards as designated under a variety of regulations and is solely the responsibility of the person offering the material for transport into commerce.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended
Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended
Benzene (CAS 71-43-2)

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended
Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended
Benzene (CAS 71-43-2)
Toluene (CAS 108-88-3)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA
Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended
Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended
Benzene (CAS 71-43-2)
Gasoline ; Low boiling naphtha - unspecified (CAS 86290-81-5)
Toluene (CAS 108-88-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.
Benzene (CAS 71-43-2)
Gasoline ; Low boiling naphtha - unspecified (CAS 86290-81-5)

Other EU regulations Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances
Hazard categories in accordance with Regulation (EC) No 1272/2008
- P5a FLAMMABLE LIQUIDS
- E2 Hazardous to the Aquatic Environment Chronic

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended
Benzene (CAS 71-43-2)

Ethanol (CAS 64-17-5)
Gasoline ; Low boiling naphtha - unspecified (CAS 86290-81-5)
Toluene (CAS 108-88-3)

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation on the protection of workers from the risks of exposure to carcinogens and mutagens at work, in accordance with Directive 2004/37/EC, as amended.
15.2. Chemical safety assessment	Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS: Chemical Abstract Service.
CEN: European Committee for Standardization.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.
TWA: Time Weighted Average.
vPvB: Very persistent and very bioaccumulative.

References

Chemical safety report.
CONCAWE
ECHA: European Chemical Agency.

Information on evaluation method leading to the classification of mixture

Not applicable.

Full text of any statements, which are not written out in full under sections 2 to 15

H224 Extremely flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer

The information in this Safety Data Sheet (SDS) was obtained from sources believed to be reliable and accurate, and is not represented as being absolutely complete. The end user of this product has the responsibility for evaluating the adequacy of the data for the intended application and conditions of use; for determining the safety, toxicity, regulatory requirements, and suitability of the product under these conditions; and for obtaining additional or clarifying data where uncertainty exists. The data serves as general guidance only, and is to be used in combination with professional judgement of persons experienced in a specific application, use or process; and additional data may be required.