



# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

<b>Material name</b>	<b>Bituminous Pavement Marker Adhesive</b>
<b>Revision date</b>	11-08-2011
<b>Version #</b>	01
<b>CAS #</b>	Mixture
<b>MSDS Number</b>	214
<b>Product use</b>	Asphalt products are to be used as road and highway paving applications; waterproofing and sealing applications; coatings; or other engineering applications. Use in other applications may result in higher exposures and require additional engineering controls and personal protective equipment.
<b>Synonym(s)</b>	See section 16 for complete information.
<b>Manufacturer/Supplier</b>	Valero Marketing & Supply Company and Affiliates P.O. Box 696000 San Antonio, TX 78269-6000
<b>General Assistance</b>	210-345-4593
<b>Emergency</b>	24 Hour Emergency 866-565-5220 1-800-424-9300 (CHEMTREC USA)

## 2. Hazards Identification

<b>Physical state</b>	Solid.
<b>Appearance</b>	Dark brown to black liquid at normal use temperatures above 300F. Semi-solid at 70F.
<b>Emergency overview</b>	<b>WARNING</b> Contact with product at elevated temperatures can result in thermal burns.  Harmful if inhaled or swallowed. May be harmful if absorbed through skin. Aspiration may cause lung damage. Irritating to eyes, respiratory system and skin. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Suspect cancer hazard - may cause cancer. Prolonged exposure may cause chronic effects. Contains polycyclic aromatic hydrocarbons (PAHs). Some PAHs are recognized carcinogens and may cause skin, lung and bladder cancer. Hydrogen sulfide, a highly toxic gas, may be present or released. Signs and symptoms of overexposure to hydrogen sulfide include respiratory and eye irritation, dizziness, nausea, coughing, a sensation of dryness and pain in the nose, and loss of consciousness. Odor does not provide a reliable indicator of the presence of hazardous levels in the atmosphere.
<b>OSHA regulatory status</b>	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
<b>Potential health effects</b>	
<b>Routes of exposure</b>	Inhalation. Ingestion. Skin contact. Eye contact.
<b>Eyes</b>	This product is normally stored, shipped or used hot (300 to 400 F). Hot, molten material can cause thermal burns. Contact may irritate or burn eyes. Eye contact may result in corneal injury.
<b>Skin</b>	This product is normally stored, shipped or used hot (300 to 400 F). Contact with hot product may cause severe burns. May be harmful if absorbed through skin. Contains a substance which has been shown to cause cancer in laboratory animals. Irritating to skin. High pressure skin injections are <b>SERIOUS MEDICAL EMERGENCIES</b> . Injuries may not appear serious at first. Within a few hours, tissues will become swollen, discolored and extremely painful.
<b>Inhalation</b>	Harmful if inhaled. Irritating to respiratory system. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. May cause breathing disorders and lung damage. Prolonged inhalation may be harmful.
<b>Ingestion</b>	Harmful if swallowed. Ingestion may result in vomiting; aspiration (breathing) of vomitus into lungs must be avoided as even small quantities may result in aspiration pneumonitis. Irritating to mouth, throat, and stomach.
<b>Target organs</b>	Eyes. Respiratory system. Skin. Central nervous system. Lungs.
<b>Chronic effects</b>	Suspect cancer hazard - may cause cancer. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**Signs and symptoms** Irritation of nose and throat. Irritation of eyes and mucous membranes. Skin irritation. Unconsciousness. Corneal damage. Narcosis. Decrease in motor functions. Behavioral changes. Edema. Conjunctivitis. Proteinuria. Defatting of the skin. Rash.

**Potential environmental effects** The product is not expected to be hazardous to the environment.

### 3. Composition / Information on Ingredients

Components	CAS #	Percent
Calcium aluminum silicates	Mixture	50 - 70
Asphalt	8052-42-4	30 - 50
Quartz	14808-60-7	1 - 6
Naphthalene	91-20-3	0 - 1
Polycyclic Aromatic Hydrocarbons	130498-29-2	0 - 1
Hydrogen sulfide	7783-06-4	<0.2

**Composition comments** Dangerous amounts of hydrogen sulfide, a highly toxic gas, may be present, especially in the headspace of containers.

### 4. First Aid Measures

#### First aid procedures

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

**Skin contact** In case of contact with hot or molten product, cool rapidly with water and seek immediate medical attention. Do not attempt to remove molten product from skin because skin will tear easily. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists. Wash clothing separately before reuse. Destroy or thoroughly clean contaminated shoes. If high pressure injection under the skin occurs, always seek medical attention.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

**Ingestion** Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Do not give mouth-to-mouth resuscitation. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Get medical attention immediately.

**Notes to physician** In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General advice** If exposed or concerned: get medical attention/advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.

### 5. Fire Fighting Measures

**Flammable properties** Not flammable by OSHA or DOT criteria.

#### Extinguishing media

**Suitable extinguishing media** Water spray. Water fog. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet.

#### Protection of firefighters

**Protective equipment and precautions for firefighters** Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

**Fire fighting equipment/instructions** Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. In the event of fire, cool tanks with water spray. Cool containers exposed to flames with water until well after the fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Water runoff can cause environmental damage. Use compatible foam to minimize vapor generation as needed.

**Specific methods** In the event of fire and/or explosion do not breathe fumes.

**Hazardous combustion products** Carbon oxides. Sulfur oxides. Nitrogen oxides. Hydrocarbons. Hydrogen sulfide.

## 6. Accidental Release Measures

<b>Personal precautions</b>	Keep unnecessary personnel away. Local authorities should be advised if significant spills cannot be contained. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the MSDS for Personal Protective Equipment.
<b>Environmental precautions</b>	If facility or operation has an "oil or hazardous substance contingency plan", activate its procedures. Stay upwind and away from spill. Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not enter or stay in area unless monitoring indicates that it is safe to do so. Isolate hazard area and restrict entry to emergency crew. Review Firefighting Measures, Section 5, before proceeding with clean up. Keep all sources of ignition (flames, smoking, flares, etc.) and hot surfaces away from release. Contain spill in smallest possible area. Recover as much product as possible (e.g. by vacuuming). Stop leak if it can be done without risk. Use water spray to disperse vapors. Use compatible foam to minimize vapor generation as needed. Spilled material may be absorbed by an appropriate absorbent, and then handled in accordance with environmental regulations. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment or drainage systems and natural waterways. Contact fire authorities and appropriate federal, state and local agencies. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, contact the National Response Center at 1-800-424-8802. For highway or railways spills, contact Chemtrec at 1-800-424-9300.
<b>Methods for containment</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Local authorities should be advised if significant spillages cannot be contained. Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.
<b>Methods for cleaning up</b>	Use only non-sparking tools.  Large Spills: Prevent product from entering drains.
<b>Other information</b>	Clean up in accordance with all applicable regulations.

## 7. Handling and Storage

<b>Handling</b>	Wear personal protective equipment. Avoid breathing mist or vapor from heated material. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only with adequate ventilation. Wash thoroughly after handling. Do not handle, store or open near an open flame or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use only non-sparking tools. When using, do not eat, drink or smoke. Avoid release to the environment.
<b>Storage</b>	Material is normally stored in closed tanks at 250 to 375F. Do not handle, store or open near an open flame or sources of ignition. Protect material from direct sunlight. This material can accumulate static charge which may cause spark and become an ignition source. The pressure in sealed containers can increase under the influence of heat. Keep container tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children.

## 8. Exposure Controls / Personal Protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Asphalt (8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.
Hydrogen sulfide (7783-06-4)	STEL	5 ppm	
Naphthalene (91-20-3)	TWA	1 ppm	
	STEL	15 ppm	
Quartz (14808-60-7)	TWA	10 ppm	
	TWA	0.025 mg/m3	Respirable fraction.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Naphthalene (91-20-3)	PEL	50 mg/m3 10 ppm

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Hydrogen sulfide (7783-06-4)	Ceiling	20 ppm

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
Quartz (14808-60-7)	TWA	0.3 mg/m3	Total dust. Respirable. Respirable.
		0.1 mg/m3	
		2.4 mppcf	

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value	Form
Asphalt (8052-42-4)	TWA	5 mg/m3	Fume.
Hydrogen sulfide (7783-06-4)	Ceiling	21 mg/m3	
Naphthalene (91-20-3)	TWA	15 ppm	
		14 mg/m3	
		10 ppm	
Naphthalene (91-20-3)	STEL	79 mg/m3	
		15 ppm	
Quartz (14808-60-7)	TWA	52 mg/m3	Respirable particles.
		10 ppm	
		0.025 mg/m3	

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value	Form
Asphalt (8052-42-4)	TWA	0.5 mg/m3	Aerosol, inhalable.
Hydrogen sulfide (7783-06-4)	Ceiling	10 ppm	
Naphthalene (91-20-3)	STEL	15 ppm	
		10 ppm	
Quartz (14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

**Canada. Ontario OELs. (Ministry of Labor - Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value	Form
Asphalt (8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
Hydrogen sulfide (7783-06-4)	STEL	21 mg/m3	
Naphthalene (91-20-3)	TWA	15 ppm	
		14 mg/m3	
		10 ppm	
Naphthalene (91-20-3)	STEL	78 mg/m3	
		15 ppm	
Quartz (14808-60-7)	TWA	52 mg/m3	Respirable fraction.
		10 ppm	
		0.1 mg/m3	

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value	Form
Asphalt (8052-42-4)	TWA	5 mg/m3	Fume.
Hydrogen sulfide (7783-06-4)	STEL	21 mg/m3	
Naphthalene (91-20-3)	TWA	15 ppm	
		14 mg/m3	
		10 ppm	
Naphthalene (91-20-3)	STEL	79 mg/m3	
		15 ppm	
Quartz (14808-60-7)	TWA	52 mg/m3	Respirable dust.
		10 ppm	
		0.1 mg/m3	

**Mexico. Occupational Exposure Limit Values**

Components	Type	Value	Form
Asphalt (8052-42-4)	STEL	10 mg/m3	Fume.
Hydrogen sulfide (7783-06-4)	TWA	5 mg/m3	Fume.
		21 mg/m3	
		15 ppm	
Hydrogen sulfide (7783-06-4)	TWA	14 mg/m3	
		10 ppm	
		10 ppm	

## Mexico. Occupational Exposure Limit Values

Components	Type	Value	Form
Naphthalene (91-20-3)	STEL	75 mg/m <sup>3</sup>	
		15 ppm	
	TWA	50 mg/m <sup>3</sup>	
		10 ppm	
Quartz (14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	

### Engineering controls

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

### Personal protective equipment

#### Eye / face protection

Wear safety glasses. If splash potential exists, wear full face shield or chemical goggles.

#### Skin protection

Wear chemical-resistant, impervious gloves. Flame retardant protective clothing is recommended.

#### Respiratory protection

Wear a NIOSH-approved (or equivalent) respirator as needed.

#### General hygiene considerations

Consult supervisor for special handling instructions. Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Wash hands before breaks and immediately after handling the product. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical & Chemical Properties

Appearance	Dark brown to black liquid at normal use temperatures above 300F. Semi-solid at 70F.
Color	Brown/black.
Odor	Strong petroleum.
Odor threshold	Not available.
Physical state	Solid.
Form	Semi-Solid at 70F
pH	Not available.
Melting point	> 135 °F (> 57.2 °C)
Freezing point	Not available.
Boiling point	700 - 1100.1 °F (371.1 - 593.4 °C)
Flash point	> 349.9 °F (> 176.6 °C) Closed Cup
Evaporation rate	Not available.
Flammability limits in air, upper, % by volume	< 7
Flammability limits in air, lower, % by volume	> 0.9
Vapor pressure	< 0.1 mmHg (20°C)
Vapor density	> 1.6 (Air = 1)
Specific gravity	1 - 1.2 (Water=1)
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 600.1 °F (> 315.6 °C)
Decomposition temperature	Not available.

## 10. Chemical Stability & Reactivity Information

### Chemical stability

Stable under normal temperature conditions and recommended use.

### Conditions to avoid

Flames and sparks. Ignition sources. Contact with incompatible materials. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

### Incompatible materials

Strong oxidizing agents.

### Hazardous decomposition products

Carbon oxides. Sulfur oxides. Nitrogen oxides. Hydrocarbons. Hydrogen sulfide.

### Possibility of hazardous reactions

Hazardous polymerization does not occur.

## 11. Toxicological Information

### Toxicological data

#### Components

#### Test Results

Hydrogen sulfide (7783-06-4)

Acute Inhalation LC50 Monkey: 0.7 mg/l 35 Minutes

Acute Inhalation LC50 Mouse: > 0.024 mg/l 960 Minutes

Acute Inhalation LC50 Rat: > 0.38 mg/l 960 Minutes

Naphthalene (91-20-3)

Acute Dermal LD50 Rabbit: > 2 g/kg

Acute Oral LD50 Rat: 490 mg/kg

#### Acute effects

Harmful if inhaled, absorbed through skin, or swallowed. Harmful: may cause lung damage if swallowed. Irritating to eyes, respiratory system and skin. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Hydrogen sulfide, a highly toxic gas, may be present. Signs and symptoms of overexposure to hydrogen sulfide include respiratory and eye irritation, dizziness, nausea, coughing, a sensation of dryness and pain in the nose, and loss of consciousness. Odor does not provide a reliable indicator of the presence of hazardous levels in the atmosphere.

#### Local effects

##### US ACGIH Threshold Limit Values: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

#### Sensitization

This substance may have a potential for sensitization which may provoke an allergic reaction among sensitive individuals.

#### Subchronic effects

Liver and kidney damage may occur after prolonged and repeated exposure.

#### Carcinogenicity

Contains polycyclic aromatic compounds (PACs). Prolonged and/or repeated skin contact with certain PACs has been shown to cause skin cancer. Prolonged and/or repeated exposures by inhalation of certain PACs may also cause cancer of the lung and of other sites of the body.

##### ACGIH Carcinogens

Asphalt (CAS 8052-42-4)

A4 Not classifiable as a human carcinogen.

Naphthalene (CAS 91-20-3)

A4 Not classifiable as a human carcinogen.

Quartz (CAS 14808-60-7)

A2 Suspected human carcinogen.

##### IARC Monographs. Overall Evaluation of Carcinogenicity

Asphalt (CAS 8052-42-4)

2B Possibly carcinogenic to humans.

Naphthalene (CAS 91-20-3)

3 Not classifiable as to carcinogenicity to humans.

Quartz (CAS 14808-60-7)

2B Possibly carcinogenic to humans.

1 Carcinogenic to humans.

##### US NTP Report on Carcinogens: Anticipated carcinogen

Naphthalene (CAS 91-20-3)

Anticipated carcinogen.

##### US NTP Report on Carcinogens: Known carcinogen

Quartz (CAS 14808-60-7)

Known carcinogen.

#### Epidemiology

Pre-existing skin conditions including dermatitis might be aggravated by exposure to this product.

#### Mutagenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a mutagen by OSHA.

#### Reproductive effects

This product is not expected to cause reproductive or developmental effects.

#### Teratogenicity

The components of this product are not reported to cause teratogenic effects in humans. Based on best current information, there is no known teratogenicity associated with this product.

#### Further information

Symptoms may be delayed.

## 12. Ecological Information

### Ecotoxicological data

#### Components

#### Test Results

Hydrogen sulfide (7783-06-4)

LC50 Lake whitefish (*Coregonus clupeaformis*): 0.002 mg/l 96 hours

Naphthalene (91-20-3)

EC50 Water flea (*Daphnia magna*): 1.09 - 3.4 mg/l 48 hours

LC50 Rainbow trout, donaldson trout (*Oncorhynchus mykiss*):  
0.91 - 2.82 mg/l 96 hours

#### Ecotoxicity

Not expected to be harmful to aquatic organisms.

<b>Persistence and degradability</b>	Not available.
<b>Bioaccumulation / Accumulation</b>	No data available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Mobility in environmental media</b>	No data available.

### 13. Disposal Considerations

**Disposal instructions** Dispose in accordance with all applicable regulations.

### 14. Transport Information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

#### TDG

Not regulated as dangerous goods.

### 15. Regulatory Information

#### US federal regulations

##### TSCA Section 12(b) Export Notification(40 CFR 707, Subpt. D)

Not regulated.

##### US CAA Section 112 Hazardous Air Pollutants (HAPs) List

NAPHTHALENE (CAS 91-20-3)

POLYCYCLIC ORGANIC MATTER (CAS 130498-29-2)

##### US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Spill: Reportable quantity

Hydrogen sulfide (CAS 7783-06-4) 100 LBS

##### US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Substance: Threshold Planning Quantity

Hydrogen sulfide (CAS 7783-06-4) 500 LBS

##### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Naphthalene (CAS 91-20-3) 0.1 %

Polycyclic Aromatic Hydrocarbons (CAS 130498-29-2) 0.1 % N590 Substance is not eligible for the de minimis exemption except for the purposes of supplier notification requirements.

##### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Reportable threshold

Polycyclic Aromatic Hydrocarbons (CAS 130498-29-2) 100 LBS N590

##### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Naphthalene (CAS 91-20-3) Listed.

Polycyclic Aromatic Hydrocarbons (CAS 130498-29-2) N590 Listed.

#### CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

Naphthalene: 100

Hydrogen sulfide: 100

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

##### Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - No

Pressure Hazard - No

Reactivity Hazard - No

##### Section 302 extremely hazardous substance (40 CRF 355, Appendix A)

No

##### Section 311/312 (40 CFR 370)

Yes

**Drug Enforcement Administration (DEA) (21 CFR 1308.11-15)**

Not controlled

**WHMIS status**

Controlled

**WHMIS classification**

D2A - Other Toxic Effects-VERY TOXIC  
D2B - Other Toxic Effects-TOXIC

**WHMIS labeling**



**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations**

**US - California Hazardous Substances (Director's): Listed substance**

Asphalt (CAS 8052-42-4) Listed.  
Hydrogen sulfide (CAS 7783-06-4) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Polycyclic Aromatic Hydrocarbons (CAS 130498-29-2) Listed.

**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Asphalt (CAS 8052-42-4) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Quartz (CAS 14808-60-7) Listed.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Asphalt (CAS 8052-42-4) Listed: January 1, 1990 Carcinogenic.  
Naphthalene (CAS 91-20-3) Listed: April 19, 2002 Carcinogenic.  
Quartz (CAS 14808-60-7) Listed: October 1, 1988 Carcinogenic.

**US - Massachusetts RTK - Substance: Listed substance**

Asphalt (CAS 8052-42-4) Listed.  
Hydrogen sulfide (CAS 7783-06-4) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Quartz (CAS 14808-60-7) Listed.

**US - New Jersey Community RTK (EHS Survey): Reportable threshold**

Hydrogen sulfide (CAS 7783-06-4) 500 LBS  
Naphthalene (CAS 91-20-3) 500 LBS  
Polycyclic Aromatic Hydrocarbons (CAS 130498-29-2) 500 LBS

**US - New Jersey RTK - Substances: Listed substance**

Asphalt (CAS 8052-42-4) Listed.  
Hydrogen sulfide (CAS 7783-06-4) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Polycyclic Aromatic Hydrocarbons (CAS 130498-29-2) Listed.  
Quartz (CAS 14808-60-7) Listed.

**US - Pennsylvania RTK - Hazardous Substances: Listed substance**

Asphalt (CAS 8052-42-4) Listed.

Hydrogen sulfide (CAS 7783-06-4)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Polycyclic Aromatic Hydrocarbons (CAS 130498-29-2)	Listed.
Quartz (CAS 14808-60-7)	Listed.

**US - Pennsylvania RTK - Hazardous Substances: Special hazard**

Asphalt (CAS 8052-42-4)	Special hazard.
-------------------------	-----------------

## 16. Other Information

### Other information

Note: This Material Safety Data Sheet applies to the listed products and synonym descriptions for Hazard Communication purposes only. Technical Specifications vary greatly depending on the products and are not reflected in this document. Consult specification sheets for technical information.

### HMIS® ratings

Health: 2\*  
Flammability: 1  
Physical hazard: 0

### NFPA ratings

Health: 2  
Flammability: 1  
Instability: 0

### Disclaimer

This Material Safety Data Sheet (MSDS) was prepared in accordance with 29 CFR 1910.1200 by Valero Marketing & Supply Co., ("VALERO"). VALERO does not assume any liability arising out of product use by others. The information, recommendations, and suggestions presented in this MSDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.

### Issue date

11-08-2011