



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name Mixed P-P's (Propane/Propylene)
Revision date 06-10-2011
Version # 01
CAS # 68606-26-8
MSDS Number 308
Product use Organic synthesis. Household and industrial fuel.
Synonym(s) Blend Of Propane and Propylene, Refinery Grade Propylene
See section 16 for complete information.
Manufacturer/Supplier Valero Marketing & Supply Company and Affiliates
P.O. Box 696000
San Antonio, TX 78269-6000
General Assistance 210-345-4593
Emergency 24 Hour Emergency 866-565-5220
1-800-424-9300 (CHEMTREC USA)

2. Hazards Identification

Physical state Gas.
Appearance Colorless liquefied gas.
Emergency overview DANGER
Extremely flammable gas. High pressure gas. Gas reduces oxygen available for breathing.
Contact with liquefied gas might cause frostbites, in some cases with tissue damage. In a fire or if heated, a pressure increase will occur and the container may burst or explode.
OSHA regulatory status This product is hazardous according to OSHA 29 CFR 1910.1200.
Potential health effects
Routes of exposure Inhalation. Eyes. Skin.
Eyes Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").
Skin Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").
Inhalation Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Nasal and respiratory tract irritation, central nervous system effects including excitation, euphoria, contracted eye pupils, dizziness, drowsiness, blurred vision, fatigue, nausea, headache, loss of reflexes, tremors, convulsions, seizures, loss of consciousness, coma, respiratory arrest and sudden death could occur as a result of long term and/or high concentration exposure to vapors. May also cause anemia and irregular heart rhythm.
Ingestion This material is a gas under normal atmospheric conditions and ingestion is unlikely.
Target organs Respiratory tract. Eyes. Central nervous system.
Chronic effects May cause central nervous system effects. Components have been shown to be weak cardiac sensitizers which can result in cardiac arrhythmia and ventricular fibrillation.
Potential environmental effects Not expected to be harmful to aquatic organisms.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Propylene	115-07-1	50 - 80
Propane	74-98-6	20 - 40
Ethane	74-84-0	0 - 10
Ethylene	74-85-1	0 - 10
Isobutane	75-28-5	0 - 1

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Skin contact	Wash frost-bitten areas with plenty of water. Do not remove clothing. Get medical attention immediately.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician or poison control center immediately.
Ingestion	Ingestion is not a typical route of exposures for gases or liquefied gases.
Notes to physician	Treat symptomatically.

5. Fire Fighting Measures

Flammable properties

Extremely flammable gas. Gas forms mixtures with air which can catch fire and burn with explosive violence. Vapors are heavier than air and invisible mixture spreads easily and may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable extinguishing media Dry chemical, CO₂, water spray, fog, or foam.

Fire fighting

equipment/instructions

Self-contained breathing apparatus, operated in positive pressure mode and full protective clothing must be worn in case of fire.

Move container from fire area if it can be done without risk.

Do not extinguish fires unless gas flow can be stopped safely; explosive re-ignition may occur. Promptly isolate the scene by removing all persons from the vicinity of the incident. No action shall be taken involving any personal risk or without suitable training. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Stop flow of material. Use water to keep fire exposed containers cool and to protect personnel effecting shutoff. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop leak. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply.

Hazardous combustion products

Carbon oxides.

6. Accidental Release Measures

Personal precautions

Evacuate the area promptly. No action shall be taken involving any personal risk or without suitable training. Keep unnecessary personnel away.

Ensure adequate ventilation. In case of inadequate ventilation, use respiratory protection. Wear appropriate personal protective equipment (See Section 8).

Environmental precautions

Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Prevent from entering into soil, ditches, sanitary sewers, waterways and/or groundwater.

Methods for cleaning up

Ventilate well, stop flow of gas or liquid if possible. Immediately contact emergency personnel.

7. Handling and Storage

Handling

Wear appropriate personal protective equipment (See Section 8). Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Do not breathe gas. Do not get in eyes, on skin, on clothing. Use only with adequate ventilation.

Storage

Store in accordance with local, regional, national, and international regulations. Secure cylinders in an upright position at all times, close all valves when not in use. Store in a cool, dry, well-ventilated place. Keep container tightly closed and sealed until ready for use. Protect cylinders from damage.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethane (74-84-0)	TWA	1000 ppm
Ethylene (74-85-1)	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Isobutane (75-28-5)	TWA	1000 ppm
Propane (74-98-6)	TWA	1000 ppm
Propylene (115-07-1)	TWA	500 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (74-98-6)	PEL	1000 ppm 1800 mg/m ³

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Ethane (74-84-0)	TWA	1000 ppm
Ethylene (74-85-1)	TWA	229 mg/m ³ 200 ppm
Propane (74-98-6)	TWA	1000 ppm
Propylene (115-07-1)	TWA	500 ppm 860 mg/m ³

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Ethane (74-84-0)	TWA	1000 ppm
Ethylene (74-85-1)	TWA	200 ppm
Isobutane (75-28-5)	TWA	1000 ppm
Propane (74-98-6)	TWA	1000 ppm
Propylene (115-07-1)	TWA	500 ppm

Canada. Ontario OELs. (Ministry of Labor - Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Ethane (74-84-0)	TWA	1000 ppm
Ethylene (74-85-1)	TWA	200 ppm
Propane (74-98-6)	TWA	1000 ppm
Propylene (115-07-1)	TWA	500 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Propane (74-98-6)	TWA	1000 ppm 1800 mg/m ³

Engineering controls Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. The engineering controls also need to keep gas, vapor, or dust concentrations below any lower explosive limits.

Personal protective equipment

Eye / face protection	Wear approved safety glasses or goggles.
Skin protection	Wear protective clothing appropriate for the risk of exposure.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
General hygiene considerations	Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practices.

9. Physical & Chemical Properties

Appearance	Colorless liquefied gas.
Color	Colorless
Odor	Odorless (but may have skunk odor added).

Odor threshold	Not available.
Physical state	Gas.
Form	Compressed liquefied gas.
pH	Not available.
Melting point	Not available.
Freezing point	-299 °F (-183.89 °C) Weighted average
Boiling point	-44 - 11.1 °F (-42.2 - -11.6 °C)
Flash point	-212.5 °F (-135.85 °C) Closed Cup (Ethylene)
Evaporation rate	Not available.
Flammability limits in air, upper, % by volume	9.5 %
Flammability limits in air, lower, % by volume	1 %
Vapor pressure	Not available.
Vapor density	1.6
Specific gravity	0.52
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 500 °F (> 260 °C)
Decomposition temperature	Not available.
VOC	100 %

10. Chemical Stability & Reactivity Information

Chemical stability	Stable under normal temperature conditions and recommended use.
Conditions to avoid	In a fire or if heated, a pressure increase will occur and the container may burst or explode.
Incompatible materials	Oxidizing agents. Reducing agents. Acids. Alkalies.
Hazardous decomposition products	None known.
Possibility of hazardous reactions	Polymerization will not occur.

11. Toxicological Information

Toxicological data

Components	Test Results
Propylene (115-07-1)	Acute Inhalation LC50 Mouse: 680 mg/l 2 Hours
Ethylene (74-85-1)	Acute Inhalation LC50 Rat: 658 mg/l 4 Hours Acute Oral LD50 Mouse: 1093 mg/l
Propane (74-98-6)	Acute Inhalation LC50 Rat: > 1442.847 mg/l 15 Minutes
Acute effects	Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").
Chronic effects	May cause central nervous system effects.
Carcinogenicity	
ACGIH Carcinogens	
Ethylene (CAS 74-85-1)	A4 Not classifiable as a human carcinogen.
Propylene (CAS 115-07-1)	A4 Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Ethylene (CAS 74-85-1)	3 Not classifiable as to carcinogenicity to humans.
Propylene (CAS 115-07-1)	3 Not classifiable as to carcinogenicity to humans.

12. Ecological Information

Ecotoxicity	Not expected to be harmful to aquatic organisms.
--------------------	--

Persistence and degradability	Not available.
Bioaccumulation / Accumulation	No data available.
Partition coefficient (n-octanol/water)	Not available.
Mobility in environmental media	No data available.

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 °F
Disposal instructions	Dispose in accordance with all applicable regulations. Empty containers may contain product residues. Do not puncture or incinerate even when empty. This material and/or its container must be disposed of as hazardous waste. Return the empty cylinder to the supplier.

14. Transport Information

DOT

Basic shipping requirements:

UN number	UN1075
Proper shipping name	Petroleum gases, liquefied
Hazard class	2.1
Labels required	2.1

Additional information:

Special provisions	T50
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	314, 315
ERG number	115

DOT BULK

Basic shipping requirements:

UN number	UN1075
Proper shipping name	Petroleum gases, liquefied
Hazard class	2.1
Labels required	2.1

Additional information:

Special provisions	T50
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	314, 315
ERG number	115

IATA

Basic shipping requirements:

UN number	1075
Proper shipping name	Petroleum gases, liquefied
Hazard class	2.1

Additional information:

ERG code	10L
-----------------	-----

IMDG

Basic shipping requirements:

UN number	1075
Proper shipping name	PETROLEUM GASES, LIQUEFIED
Hazard class	2.1
EmS No.	F-D*, S-U

TDG

Basic shipping requirements:

Proper shipping name	PETROLEUM GASES, LIQUEFIED
Hazard class	2.1

UN number UN1075

15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification(40 CFR 707, Subpt. D)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Ethylene (CAS 74-85-1) 1.0 %
Propylene (CAS 115-07-1) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Ethylene (CAS 74-85-1) Listed.
Propylene (CAS 115-07-1) Listed.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

Propylene: 100
Propane: 100
Ethane: 100
Ethylene: 100
Isobutane: 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

Section 302 extremely hazardous substance (40 CFR 355, Appendix A) Yes

Section 311/312 (40 CFR 370) Yes

Clean Water Act (CWA) Section 112(r) (40 CFR 68.130) Hazardous substance

Drug Enforcement Administration (DEA) (21 CFR 1308.11-15) Not controlled

Canadian regulations This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS status Controlled

WHMIS classification A - Compressed Gas
B1 - Flammable/Combustible
D2B - Other Toxic Effects-TOXIC

WHMIS labeling



Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

US - California Hazardous Substances (Director's): Listed substance

Propylene (CAS 115-07-1) Listed.

US - Massachusetts RTK - Substance: Listed substance

Ethane (CAS 74-84-0) Listed.

Ethylene (CAS 74-85-1) Listed.

Isobutane (CAS 75-28-5) Listed.

Propane (CAS 74-98-6) Listed.

Propylene (CAS 115-07-1) Listed.

US - New Jersey Community RTK (EHS Survey): Reportable threshold

Ethane (CAS 74-84-0) 500 LBS

Ethylene (CAS 74-85-1) 500 LBS

Isobutane (CAS 75-28-5) 500 LBS

Propane (CAS 74-98-6) 500 LBS

Propylene (CAS 115-07-1) 500 LBS

US - New Jersey RTK - Substances: Listed substance

Ethane (CAS 74-84-0) Listed.

Ethylene (CAS 74-85-1) Listed.

Isobutane (CAS 75-28-5) Listed.

Propane (CAS 74-98-6) Listed.

Propylene (CAS 115-07-1) Listed.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

Ethane (CAS 74-84-0) Listed.

Ethylene (CAS 74-85-1) Listed.

Isobutane (CAS 75-28-5) Listed.

Propane (CAS 74-98-6) Listed.

Propylene (CAS 115-07-1) Listed.

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

Other information

Note: This Material Safety Data Sheet applies to the listed products and synonym descriptions for Hazard Communication purposes only. Technical Specifications vary greatly depending on the products and are not reflected in this document. Consult specification sheets for technical information.

HMIS® ratings

Health: 1
Flammability: 4
Physical hazard: 0

NFPA ratings

Health: 2
Flammability: 4
Instability: 0

Disclaimer

This Material Safety Data Sheet (MSDS) was prepared in accordance with 29 CFR 1910.1200 by Valero Marketing & Supply Co., ("VALERO"). VALERO does not assume any liability arising out of product use by others. The information, recommendations, and suggestions presented in this MSDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.

Issue date

06-10-2011