



SAFETY DATA SHEET

1. Identification

Product identifier Mixed P-P's (Propane/Propylene)

Other means of identification

SDS number 308

Synonyms Blend Of Propane and Propylene, Refinery Grade Propylene
See section 16 for complete information.

Recommended use Organic synthesis. Household and industrial fuel.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier Valero Marketing & Supply Company and Affiliates
One Valero Way
San Antonio, TX 78269-6000
210-345-4593
CorpHSE@valero.com

General Assistance 210-345-4593

E-Mail CorpHSE@valero.com

Contact Person Industrial Hygienist

Emergency Telephone 24 Hour Emergency 866-565-5220
1-800-424-9300 (CHEMTREC USA)

2. Hazard(s) identification

Physical hazards Flammable gases Category 1
Gases under pressure Liquefied gas

Health hazards Not classified.

OSHA defined hazards Simple asphyxiant

Label elements



Signal word Danger

Hazard statement Extremely flammable gas. Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Response Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.

Storage Protect from sunlight. Store in a well-ventilated place.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Propylene	115-07-1	50 - 80
Propane	74-98-6	20 - 40
Ethane	74-84-0	0 - 10
Ethylene	74-85-1	0 - 10

4. First-aid measures

Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician or poison control center immediately.
Skin contact	Wash frost-bitten areas with plenty of water. Do not remove clothing. Get medical attention immediately.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Ingestion is not a typical route of exposure for gases or liquefied gases.
Most important symptoms/effects, acute and delayed	Narcosis. Behavioral changes. Decrease in motor functions.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemical, CO2, water spray, fog, or foam.
Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	Extremely flammable gas. During fire, gases hazardous to health may be formed. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Self-contained breathing apparatus, operated in positive pressure mode and full protective clothing must be worn in case of fire. Move container from fire area if it can be done without risk. Do not extinguish fires unless gas flow can be stopped safely; explosive re-ignition may occur. Promptly isolate the scene by removing all persons from the vicinity of the incident. No action shall be taken involving any personal risk or without suitable training. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Stop flow of material. Use water to keep fire exposed containers cool and to protect personnel effecting shutdown. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop leak. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Evacuate the area promptly. No action shall be taken involving any personal risk or without suitable training. Keep unnecessary personnel away.
Methods and materials for containment and cleaning up	Ensure adequate ventilation. In case of inadequate ventilation, use respiratory protection. Wear appropriate personal protective equipment (See Section 8). Ventilate well, stop flow of gas or liquid if possible. Immediately contact emergency personnel.
Environmental precautions	Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Prevent from entering into soil, ditches, sanitary sewers, waterways and/or groundwater.

7. Handling and storage

Precautions for safe handling	Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Wear appropriate personal protective equipment (See Section 8). Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Do not breathe gas. Do not get in eyes, on skin, on clothing. Use only with adequate ventilation.
Conditions for safe storage, including any incompatibilities	Store in accordance with local, regional, national, and international regulations. Secure cylinders in an upright position at all times, close all valves when not in use. Store in a cool, dry, well-ventilated place. Keep container tightly closed and sealed until ready for use. Protect cylinders from damage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethylene (CAS 74-85-1)	TWA	200 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Propylene (CAS 115-07-1)	TWA	500 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Isobutane (CAS 75-28-5)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. The engineering controls also need to keep gas, vapor, or dust concentrations below any lower explosive limits.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear approved safety glasses or goggles.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear protective clothing appropriate for the risk of exposure.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practices.

9. Physical and chemical properties

Appearance	Colorless liquefied gas.
Physical state	Gas.
Form	Compressed liquefied gas.
Color	Colorless
Odor	Odorless (but may have skunk odor added).
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-299 °F (-183.89 °C) Weighted average
Initial boiling point and boiling range	-43.96 - 11.12 °F (-42.2 - -11.6 °C)
Flash point	-212.5 °F (-135.9 °C) Closed Cup (Ethylene)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1 %
Flammability limit - upper (%)	9.5 %

Mixed P-P's (Propane/Propylene)

914062 Version #: 02 Revision date: 23-May-2014 Print date: 23-May-2014

Prepared by 3E Company

Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	1.6
Relative density	0.52
Solubility(ies)	
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 500 °F (> 260 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC (Weight %)	100 %

10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Stable under normal temperature conditions and recommended use.
Possibility of hazardous reactions	Polymerization will not occur.
Conditions to avoid	In a fire or if heated, a pressure increase will occur and the container may burst or explode.
Incompatible materials	Oxidizing agents. Reducing agents. Acids. Alkalis.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Not likely, due to the form of the product.
Inhalation	Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness. Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels.
Skin contact	Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.
Eye contact	Contact with liquefied gas may cause frostbite.

Symptoms related to the physical, chemical and toxicological characteristics	Narcosis. Behavioral changes. Decrease in motor functions.
---	--

Information on toxicological effects

Acute toxicity	Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").
-----------------------	--

Components	Species	Test Results
Ethylene (CAS 74-85-1)		
Acute		
<i>Oral</i>		
LD50	Mouse	1093 mg/l
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 1442 mg/l, 15 Minutes

Components	Species	Test Results
Propylene (CAS 115-07-1)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Skin corrosion/irritation	Contact with liquefied gas might cause frostbites, in some cases with tissue damage.	
Serious eye damage/eye irritation	Direct contact with liquefied gas may cause eye damage from frostbite.	
Respiratory or skin sensitization		
Respiratory sensitization	Based on available data, the classification criteria are not met.	
Skin sensitization	Not a skin sensitizer.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity		
IARC Monographs. Overall Evaluation of Carcinogenicity		
Ethylene (CAS 74-85-1)	3 Not classifiable as to carcinogenicity to humans.	
Propylene (CAS 115-07-1)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	Based on available data, the classification criteria are not met.	
Chronic effects	May cause central nervous system effects.	
12. Ecological information		
Ecotoxicity	Not expected to be harmful to aquatic organisms.	
Persistence and degradability	Not available.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
Ethane (CAS 74-84-0)	1.81	
Ethylene (CAS 74-85-1)	1.13	
Propane (CAS 74-98-6)	2.36	
Propylene (CAS 115-07-1)	1.77	
Mobility in soil	Not available.	
Other adverse effects	Not available.	
13. Disposal considerations		
Disposal instructions	Dispose in accordance with all applicable regulations. Empty containers may contain product residues. Do not puncture or incinerate even when empty. This material and/or its container must be disposed of as hazardous waste. Return the empty cylinder to the supplier.	
Hazardous waste code	D001: Waste Flammable material with a flash point <140 °F	
Waste from residues / unused products	Dispose of in accordance with local regulations.	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.	
14. Transport information		
DOT		
UN number	UN1075	
UN proper shipping name	Petroleum gases, liquefied	
Transport hazard class(es)		
Class	2.1	
Subsidiary risk	-	
Packing group	Not applicable.	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	

Mixed P-P's (Propane/Propylene)

914062 Version #: 02 Revision date: 23-May-2014 Print date: 23-May-2014

Prepared by 3E Company

Special provisions T50
Packaging exceptions 306
Packaging non bulk 304
Packaging bulk 314, 315

IATA

UN number UN1075
UN proper shipping name Petroleum gases, liquefied
Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
 Label(s) 2.1
Packing group Not applicable.
Environmental hazards No
ERG Code 10L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1075
UN proper shipping name PETROLEUM GASES, LIQUEFIED
Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
 Label(s) 2.1
Packing group Not applicable.
Environmental hazards
 Marine pollutant No
EmS F-D*, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable. This product is a compressed or liquefied gas and when transported in bulk is covered under IGC code.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
 All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethane (CAS 74-84-0)	LISTED
Ethylene (CAS 74-85-1)	LISTED
Isobutane (CAS 75-28-5)	LISTED
Propane (CAS 74-98-6)	LISTED
Propylene (CAS 115-07-1)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Propylene	115-07-1	50 - 80

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylene	74-85-1	0 - 10

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ethane (CAS 74-84-0)
 Ethylene (CAS 74-85-1)
 Isobutane (CAS 75-28-5)
 Propane (CAS 74-98-6)
 Propylene (CAS 115-07-1)

Clean Water Act (CWA) Section 112(r) (40 CFR 68.130) Hazardous substance

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

WARNING: Byproducts of the combustion of propane contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

California requires all "persons in the course of doing business" whose products are sold in California to comply with Proposition 65 (Cal. Health and Safety Code Sections 25249.6 et seq.). Accordingly, resellers of this product in California shall comply with Proposition 65, including the provision of any necessary warnings for exposure to chemicals listed by the State of California: http://oehha.ca.gov/prop65/prop65_list/files/P65single111811.pdf

US. Massachusetts RTK - Substance List

Ethane (CAS 74-84-0)
 Ethylene (CAS 74-85-1)
 Isobutane (CAS 75-28-5)
 Propane (CAS 74-98-6)
 Propylene (CAS 115-07-1)

US. New Jersey Worker and Community Right-to-Know Act

Ethane (CAS 74-84-0)
 Ethylene (CAS 74-85-1)
 Isobutane (CAS 75-28-5)
 Propane (CAS 74-98-6)
 Propylene (CAS 115-07-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethane (CAS 74-84-0)
 Ethylene (CAS 74-85-1)
 Isobutane (CAS 75-28-5)
 Propane (CAS 74-98-6)
 Propylene (CAS 115-07-1)

US. Rhode Island RTK

Ethane (CAS 74-84-0)
 Ethylene (CAS 74-85-1)
 Isobutane (CAS 75-28-5)
 Propane (CAS 74-98-6)
 Propylene (CAS 115-07-1)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No


Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-June-2013
Revision date	23-May-2014
Version #	02
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA Ratings	



Disclaimer

This material Safety Data Sheet (SDS) was prepared in accordance with 29 CFR 1910.1200 by Valero Marketing & Supply Co., ("VALERO"). VALERO does not assume any liability arising out of product use by others. The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.