

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Unfinished Kero
Registration number	01-2119485517-27-0037
Synonyms	None.
SDS number	2028
Issue date	28-July-2011
Version number	05
Revision date	27-June-2013
Supersedes date	17-August-2012

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Distribution of a substance. Manufacture of substance. Formulation & (re) packaging of substances and mixtures. Use as a Fuel.
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	Valero Energy Ltd
Address	1 Westferry Circus Canary Wharf London E14 4HA UK
Telephone	01/210 345 4593 (General information; US)
e-mail	CorpHSE@valero.com
Contact person	Industrial Hygienist

1.4. Emergency telephone number 0044/(0)18 65 407333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification R10, Xn;R65, Xi;R38, N;R51/53

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
-------------------	------------	-------------------------------------

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

Hazard summary

Physical hazards	Flammable.
Health hazards	Irritating to skin. Also harmful: may cause lung damage if swallowed.
Environmental hazards	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Specific hazards	Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema/chapping and oil acne. Prolonged and repeated contact with the product may cause skin cancer. Components of the product may be absorbed into the body through the skin. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Material will float and can be re-ignited on surface of water.
Main symptoms	Irritation of eyes and mucous membranes. Skin irritation. Dermatitis. Ingestion may cause irritation and malaise.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Kerosine (petroleum)

Hazard pictograms



Signal word Danger

Hazard statements
H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P331 - Do NOT induce vomiting.

Storage
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information Not applicable.

2.3. Other hazards

Static accumulator - Static accumulating flammable materials can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite material and vapor may cause flash fire (or explosion).

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Kerosine (petroleum)	<100	8008-20-6 232-366-4	01-2119485517-27-0037	649-404-00-4	
Classification:		DSD: R10, Xn;R65, Xi;R38, N;R51-53			
		CLP: Flam. Liq. 3;H226, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Aquatic Chronic 2;H411			

CLP: Regulation No. 1272/2008.
DSD: Directive 67/548/EEC.

Composition comments

The product is a UVCB substance. The full text for all R- and H-phrases is displayed in section 16. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

General information

If exposed or concerned: get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.

4.1. Description of first aid measures

Inhalation
Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Skin contact
Remove contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops or persists. Wash clothing separately before reuse. Destroy or thoroughly clean contaminated shoes. If high pressure injection under the skin occurs, always seek medical attention.

Eye contact
Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

Ingestion	Rinse mouth thoroughly. Do not induce vomiting without advice from poison control centre. Do not give mouth-to-mouth resuscitation. Get medical attention immediately.
4.2. Most important symptoms and effects, both acute and delayed	Skin irritation. Defatting of the skin. Rash. May cause eye irritation on direct contact. Cyanosis (blue tissue condition, nails, lips, and/or skin). Narcosis. Unconsciousness. Decrease in motor functions. Behavioural changes. Aspiration may cause pulmonary oedema and pneumonitis. Jaundice. Liver enlargement. Oedema. Proteinuria.
4.3. Indication of any immediate medical attention and special treatment needed	Treat symptomatically. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures. Containers may explode when heated.
5.1. Extinguishing media	
Suitable extinguishing media	Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
5.2. Special hazards arising from the substance or mixture	Vapor may cause flash fire. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Special fire fighting procedures	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Withdraw immediately in case of rising sound from venting safety devices or any discolouration of tanks due to fire. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. In the event of fire, cool tanks with water spray. Cool containers exposed to flames with water until well after the fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Vapours may form explosive air mixtures even at room temperature. Prevent buildup of vapours or gasses to explosive concentrations. Some of these materials, if spilled, may evaporate leaving a flammable residue. Water runoff can cause environmental damage.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
For emergency responders	Keep unnecessary personnel away. Wear protective clothing as described in Section 8 of this safety data sheet.
6.2. Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. If facility or operation has an "oil or hazardous substance contingency plan", activate its procedures. Stay upwind and away from spill. Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not enter or stay in area unless monitoring indicates that it is safe to do so. Isolate hazard area and restrict entry to emergency crew. Extremely flammable. Review Fire and Explosion Hazard Data before proceeding with clean up. Keep all sources of ignition (flames, smoking, flares, etc.) and hot surfaces away from release. Contain spill in smallest possible area. Recover as much product as possible (e.g., by vacuuming). Stop leak if it can be done without risk. Use water spray to disperse vapors. Spilled material may be absorbed by an appropriate absorbent, and then handled in accordance with environmental regulations. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment or drainage systems and natural waterways. Contact fire authorities and appropriate federal, state and local agencies.

6.3. Methods and material for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Small Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Cover with plastic sheet to prevent spreading. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. Wipe up with absorbent material (e.g. cloth, fleece).

Never return spills in original containers for re-use. Prevent entry into waterways, sewers, basements or confined areas. Stop leak if you can do so without risk. This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Should not be released into the environment. This material and its container must be disposed of as hazardous waste. Use non-sparking tools and explosion-proof equipment.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Before entering storage tanks and commencing any operation in a confined area check the atmosphere for oxygen content and flammability. Provide adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid inhalation of vapours. Wear appropriate personal protective equipment. The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures. Ground container and transfer equipment to eliminate static electric sparks. Vapours are heavier than air and may travel along the floor and in the bottom of containers. Immediately change contaminated clothes. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Follow rules for flammable liquids. Keep away from heat, sparks and open flame. Keep in a cool, well-ventilated place. Keep away from food, drink and animal feeding stuffs. Store away from incompatible materials.

7.3. Specific end use(s)

For detailed information, see section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Material	Type	Value	Form
Kerosine (petroleum) (CAS 8008-20-6)	TWA	200 mg/m ³	Vapor.
Components	Type	Value	Form
Kerosine (petroleum) (CAS 8008-20-6)	TWA	200 mg/m ³	Vapor.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Material	Type	Value
Kerosine (petroleum) (CAS 8008-20-6)	TWA	300 mg/m ³
Components	Type	Value
Kerosine (petroleum) (CAS 8008-20-6)	TWA	300 mg/m ³

Italy. OELs

Material	Type	Value	Form
Kerosine (petroleum) (CAS 8008-20-6)	TWA	200 mg/m ³	Non-aerosol.
Components	Type	Value	Form
Kerosine (petroleum) (CAS 8008-20-6)	TWA	200 mg/m ³	Non-aerosol.

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Material	Type	Value
Kerosine (petroleum) (CAS 8008-20-6)	STEL	300 mg/m ³

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Material	Type	Value
	TWA	100 mg/m3
Components	Type	Value
Kerosine (petroleum) (CAS 8008-20-6)	STEL	300 mg/m3
	TWA	100 mg/m3

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Kerosine (petroleum) (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL)

Material	Type	Route	Value	Form
Kerosine (petroleum) (CAS 8008-20-6)	Workers	Inhalation	40 mg/kg/24h	Long term exposure systemic effects

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering controls Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Keep working clothes separately. Launder contaminated clothing before reuse.

Eye/face protection Wear safety glasses. If splash potential exists, wear full face shield or chemical goggles.

Skin protection

- Hand protection Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Wear suitable gloves tested to EN374.

- Other Wear chemical-resistant, impervious gloves. Full body suit and boots are recommended when handling large volumes or in emergency situations. Flame retardant protective clothing is recommended.

Respiratory protection Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards When material is heated, wear gloves to protect against thermal burns.

Hygiene measures Consult supervisor for special handling instructions. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practices.

Environmental exposure controls Contain spills and prevent releases and observe national regulations on emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colorless to yellow liquid.

Physical state Liquid.

Form Liquid.

Colour Colorless to yellow.

Odour Petroleum.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range	90 - 320 °C (194 - 608 °F)
Flash point	29,0 - 70,0 °C (84,2 - 158,0 °F)
Evaporation rate	No data available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0,7 % v/v
Flammability limit - upper (%)	5 % v/v
Vapour pressure	<1 - 3,7 (kPa) (37,8°C)
Vapour density	5,7
Relative density	750 - 840 kg/m ³ (15°C)
Solubility(ies)	Insoluble in water.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	220 - 250 °C (428 - 482 °F)
Decomposition temperature	Not available.
Viscosity	1 - 2,4 cSt (40°C)
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
9.2. Other information	
Density	0,77 - 0,85 g/cm ³ (15°C)

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Stable under normal temperature conditions and recommended use.
10.3. Possibility of hazardous reactions	Hazardous reactions do not occur.
10.4. Conditions to avoid	Heat, flames and sparks. Ignition sources. Contact with incompatible materials. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.
10.5. Incompatible materials	Strong acids. Strong oxidizers such as nitrates, chlorates, peroxides.
10.6. Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Ingestion	Ingestion may cause irritation and malaise. Swallowing or vomiting of the liquid may result in aspiration into the lungs.
Inhalation	Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and loss of co-ordination. Continued inhalation may result in unconsciousness.
Skin contact	Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May be absorbed through the skin.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms	May cause eye irritation on direct contact. Narcosis. Unconsciousness. Behavioural changes. Decrease in motor functions. Cyanosis (blue tissue condition, nails, lips, and/or skin). Jaundice. Proteinuria. Liver enlargement. Conjunctivitis. Corneal damage. Defatting of the skin. Rash. Oedema.

11.1. Information on toxicological effects

Acute toxicity	Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and loss of co-ordination. Continued inhalation may result in unconsciousness. May irritate and cause stomach pain, vomiting, diarrhoea and nausea. Human evidence indicates that the product has very low acute oral, dermal or inhalation toxicity. However, it can produce severe injury if taken into the lung as a liquid, and there may be profound central nervous system depression following prolonged exposure to high levels of vapour.
-----------------------	---

Product	Species	Test results
Kerosine (petroleum) (CAS 8008-20-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5280 mg/m3
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	Based on available data, the classification criteria are not met.	
Reproductive toxicity	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Mixture versus substance information	Not applicable.	
Other information	Symptoms may be delayed.	

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Product	Species	Test results
Kerosine (petroleum) (CAS 8008-20-6)		
Aquatic		
Algae	EL50	Algae 1 - 3 mg/l, 72 Hours
Crustacea	EL50	Daphnia magna 1,4 mg/l, 48 Hours
Fish	LL50	Oncorhynchus mykiss 2 - 5 mg/l, 96 Hours

12.2. Persistence and degradability An evaluation of representative hydrocarbon structures indicates some structures meet the persistent (P) or very persistent (vP) criteria.

12.3. Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient n-octanol/water (log Kow) Not available.

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not available.

Mobility in general The product is insoluble in water. It will spread on the water surface while some of the components will eventually sediment in water systems. The volatile components of the product will spread in the atmosphere.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects Toxic to aquatic life with long lasting effects. The product contains volatile organic compounds which have a photochemical ozone creation potential. Oil spills are generally hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

EU waste code 13 07 02*
13 07 03*
Waste codes should be assigned by the user based on the application for which the product was used.

Disposal methods/information Dispose in accordance with all applicable regulations. This material and its container must be disposed of as hazardous waste. Do not discharge into drains, water courses or onto the ground.

SECTION 14: Transport information

ADR

14.1. UN number UN1223
14.2. UN proper shipping name Kerosene
14.3. Transport hazard class(es) 3
Subsidiary class(es) -
14.4. Packing group III
14.5. Environmental hazards Yes
Tunnel restriction code D/E
Labels required 3
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number UN1223
14.2. UN proper shipping name Kerosene
14.3. Transport hazard class(es) 3
Subsidiary class(es) -
14.4. Packing group III
14.5. Environmental hazards Yes
Labels required 3
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number UN1223
14.2. UN proper shipping name Kerosene
14.3. Transport hazard class(es) 3
Subsidiary class(es) -
14.4. Packing group III
14.5. Environmental hazards Yes
Labels required 3
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number UN1223
14.2. UN proper shipping name Kerosene
14.3. Transport hazard class(es) 3
Subsidiary class(es) -
14.4. Packing group III
14.5. Environmental hazards Yes
Labels required 3
ERG code 3L
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

14.1. UN number UN1223
14.2. UN proper shipping name KEROSENE
14.3. Transport hazard class(es) 3
Subsidiary class(es) -
14.4. Packing group III

14.5. Environmental hazards

Marine pollutant Yes

Labels required 3

EmS F-E, S-E

14.6. Special precautions for user Read safety instructions, MSDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable. However, this product is a liquid and if transported in bulk covered under MARPOL 73/78, Annex I.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not regulated.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Not regulated.

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not regulated.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Kerosine (petroleum) (CAS 8008-20-6)

Directive 94/33/EC on the protection of young people at work

Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended and respective national laws implementing EC directives. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. 96/82/EC (Seveso II) Directive; Part 2 (Classified Substances) - Dangerous for the Environment (i)

National regulations

Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out.

SECTION 16: Other information

List of abbreviations

DSD: Directive 67/548/EEC.
CLP: Regulation No. 1272/2008.
DNEL: Derived No-Effect Level.
PNEC: Predicted No-Effect Concentration.
PBT: Persistent, bioaccumulative and toxic.
vPvB: Very Persistent and very Bioaccumulative.
eSDS: extended Safety Data Sheet.
STP: Sewage Treatment Plant.

References

Chemical safety report.
CLP files – <http://concaawe.org/>

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.
R38 Irritating to skin.
R51 Toxic to aquatic organisms.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53 May cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

This SDS contains revisions in the following section(s):

This safety data sheet contains revisions in the following section(s): 1, 3, 4, 6, 7, 8, 9, 11, 12, 14, 16.

Training information

Follow training instructions when handling this material.

Disclaimer

This material Safety Data Sheet (SDS) was prepared in accordance with EC No 1272/2008 by Valero Energy Ltd. Valero Energy Ltd. does not assume any liability arising out of product use by others. The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.

Annex to the extended Safety Data Sheet (eSDS)

1 - Exposure Scenario Worker

1. Distribution of substance

List of use descriptors

Sector(s) of Use SU3: Industrial uses.

Product categories [PC]: Not available.

Name of contributing environmental scenario and corresponding ERC

ERC1: Manufacture of substances.

ERC2: Formulation of preparations.

ERC3: Formulation in materials.

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles.

ERC5: Industrial use resulting in inclusion into or onto a matrix.

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates).

ERC6b: Industrial use of reactive processing aids.

ERC6c: Industrial use of monomers for manufacture of thermoplastics.

ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers.

ERC7: Industrial use of substances in closed systems.

Specific Environmental Release Category: ESVOC SpERC 1.1b.v1

List of names of contributing worker scenarios and corresponding PROCs

PROC1: Use in closed process, no likelihood of exposure.

PROC2: Use in closed, continuous process with occasional controlled exposure.

PROC3: Use in closed batch process (synthesis or formulation).

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises.

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).

PROC15: Use as laboratory reagent.

Further explanations

Other Process or activity

Bulk loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading, maintenance and associated laboratory activities.

2.1. Contributing exposure scenario controlling environmental exposure for Manufacture of substances.

Product characteristics

Concentration of the substance in a mixture

Covers percentage substance in the product up to 100 % (unless stated differently). Substance is complex UVCB. Predominantly hydrophobic.

Physical state

Liquid

Viscosity

Kinematic viscosity 1,6 mm²/s 40 °C

Dynamic viscosity Not available.

Amounts used

Fraction of EU tonnage used in region: 0,1

Regional use tonnage (tons/year): 5,4 e6

Fraction of Regional tonnage used locally: 0,002

Annual site tonnage (tons/year): 1,1 e4

Maximum daily site tonnage (kg/day): 3,6 e4

Frequency and duration of use

Batch process Not available.

Continuous process Emission days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0,001	0,00001	0,00001	

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Treat air emission to provide a typical removal efficiency of (%): 90
Soil Not available.
Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): 0. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): 0
Sediment Not available.
Remarks Risk from environmental exposure is driven by freshwater sediment. No wastewater treatment required.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant**Size of municipal sewage system/treatment plant (m3/d)**

Type Municipal STP
Discharge rate 2000
Treatment effectiveness 94,7
Sludge treatment technique Not available.
Measures to limit air emissions Not available.
Remarks Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d): 2,6e6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) 94,7

Conditions and measures related to external treatment of waste for disposal**Fraction of used amount transferred to external waste treatment**

Suitable waste treatment Not available.
Disposal methods Not available.
Treatment effectiveness Not available.
Remarks External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste**Fraction of used amount transferred to external waste treatment**

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.
Treatment effectiveness Not available.
Remarks Not available.

Additional good practice advice beyond the REACH CSA Additional information on the basis for the allocation of the indentified OCs and RMMs is contained in the PETRORISK file.

2.2. Contributing exposure scenario controlling worker exposure for Use in closed process, no likelihood of exposure.

Process categories beyond the REACH CSA

Use in closed, continuous process with occasional controlled exposure.
 Use in closed batch process (synthesis or formulation).
 Use in batch and other process (synthesis) where opportunity for exposure arises.
 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.
 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.
 Transfer of substance or preparation into small containers (dedicated filling line, including weighing).
 Use as laboratory reagent.

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).
Physical form of the product Liquid
Vapour pressure Liquid, vapour pressure 0,5 - 10 kPa at STP.
Process temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Amounts used

Not available.

Frequency and duration of use

	Duration	Frequency of use	Remarks
Covers daily exposures up to 8 hours (unless stated differently).	8	1 hours per day	Assumes a good basic standard of occupational hygiene is implemented.

Human factors not influenced by risk management

Exposed skin areas Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Other given operational conditions affecting workers exposure

Area of use	Room size	Temperature	Ventilation rate	Remarks

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Not available.
Technical conditions and measures to control dispersion from source towards the worker Not available.
Organizational measures to prevent/limit releases, dispersion and exposure Not available.
Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. wash off any skin contamination immediately. provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

3. Exposure Estimation

Environment

See PETRORISK file in IUCLID Section 13 - "LocalCSR" worksheet.

Health

	Exposure level	RCR	Method	Remarks
General exposures (closed systems)	0,01 ppm	0	**	Inhalation Exposure
General exposures (closed systems)	10 ppm	0.250	**	Inhalation Exposure
General exposures (closed systems)	25 ppm	0.625	**	Inhalation Exposure

General exposures (open systems)	20 ppm	0.500	**	Inhalation Exposure
Process sampling	25 ppm	0.625	**	Inhalation Exposure
Laboratory activities	10 ppm	0.250	**	Inhalation Exposure
Bulk transfers	5 ppm	0.125	**	Inhalation Exposure
Drum and small package filling	50 ppm	0.125	**	Inhalation Exposure
Equipment cleaning and maintenance	50 ppm	0.250	**	Inhalation Exposure
Bulk product storage	10 ppm	0.250	**	Inhalation Exposure

** - The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Health

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.

Available hazard data do not support the need for a DNEL to be established for other health effects. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2 - Exposure Scenario Worker

1. Manufacture of substances

List of use descriptors

Sector(s) of Use SU3: Industrial uses.
SU8: Manufacture of bulk, large scale chemicals (including petroleum products).
SU9: Manufacture of fine chemicals.

Product categories [PC]: Not available.

Name of contributing environmental scenario and corresponding ERC ERC1: Manufacture of substances.
ERC4: Industrial use of processing aids in processes and products, not becoming part of articles.
Specific Environmental Release Category: ESVOC SpERC 1.1.v1

List of names of contributing worker scenarios and corresponding PROCs PROC1: Use in closed process, no likelihood of exposure.
PROC2: Use in closed, continuous process with occasional controlled exposure.
PROC3: Use in closed batch process (synthesis or formulation).
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises.
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.
PROC15: Use as laboratory reagent.

Further explanations

Other Process or activity Manufacture of substance or use as an intermediate, process chemical or extracting agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

2.1. Contributing exposure scenario controlling environmental exposure for Manufacture of substances.

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).
Substance is complex UVCB. Predominantly hydrophobic.

Physical state Liquid

Viscosity

Kinematic viscosity 1,6 mm²/s 40 °C

Dynamic viscosity Not available.

Amounts used

Fraction of EU tonnage used in region: 0,1

Regional use tonnage (tons/year): 5,4 e6

Fraction of Regional tonnage used locally: 0,11

Annual site tonnage (tons/year): 6 e5

Maximum daily site tonnage (kg/day): 2 e6

Frequency and duration of use

Batch process Not available.

Continuous process Emission days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0,01	0,0001	0,0003	

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Treat air emission to provide a typical removal efficiency of (%): 90
Soil	Not available.
Water	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): 97,7. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): 56,1
Sediment	Not available.
Remarks	Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Onsite wastewater treatment required.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant**Size of municipal sewage system/treatment plant (m3/d)**

Type	Municipal STP
Discharge rate	10000
Treatment effectiveness	94,7
Sludge treatment technique	Not available.
Measures to limit air emissions	Not available.
Remarks	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d): 2,0e6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	97,7

Conditions and measures related to external treatment of waste for disposal**Fraction of used amount transferred to external waste treatment**

Suitable waste treatment	Not available.
Disposal methods	Not available.
Treatment effectiveness	Not available.
Remarks	During manufacturing no waste of the substance is generated.

Conditions and measures related to external recovery of waste**Fraction of used amount transferred to external waste treatment**

Suitable recover operations	During manufacturing no waste of the substance is generated to recover.
Treatment effectiveness	Not available.
Remarks	Not available.

Additional good practice advice beyond the REACH CSA Additional information on the basis for the allocation of the identified OCs and RMMs is contained in the PETRORISK file.

2.2. Contributing exposure scenario controlling worker exposure for Use in closed process, no likelihood of exposure.

Process categories beyond the REACH CSA Use in closed, continuous process with occasional controlled exposure.
 Use in closed batch process (synthesis or formulation).
 Use in batch and other process (synthesis) where opportunity for exposure arises.
 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.
 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.
 Use as laboratory reagent.

Product characteristics

Concentration of the substance in a mixture	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical form of the product	Liquid
Vapour pressure	Liquid, vapour pressure 0,5 - 10 kPa at STP.
Process temperature	Operation is carried out at elevated temperature (> 20°C above ambient temperature).

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management**Other given operational conditions affecting workers exposure**

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Not available.

Technical conditions and measures to control dispersion from source towards the worker Not available.

Organizational measures to prevent/limit releases, dispersion and exposure General measures (skin irritants); Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. wash off any skin contamination immediately. provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluations Not available.

3. Exposure Estimation**Environment**

Not available.

Health

	Exposure level	RCR	Method	Remarks
General exposures (closed systems)	0,01 ppm	0	**	Inhalation Exposure
General exposures (closed system) + With sample collection	10 ppm	0.250	**	Inhalation Exposure
General exposures (closed systems)	25 ppm	0.625	**	Inhalation Exposure
General exposures (open systems)	20 ppm	0.500	**	Inhalation Exposure
Bulk transfers	5 ppm	0.125	**	Inhalation Exposure
Sample collection	25 ppm	0.625	**	Inhalation Exposure
Laboratory activities	10 ppm	0.250	**	Inhalation Exposure
Clean down and Maintenance	50 ppm	0.250	**	Inhalation Exposure
Storage	10 ppm	0.250	**	Inhalation Exposure

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Health

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.

Available hazard data do not support the need for a DNEL to be established for other health effects. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3 - Exposure Scenario Worker

1. Formulation [mixing] of preparations and/or re-packaging

List of use descriptors

Sector(s) of Use

SU3: Industrial uses.
SU10: Formulation [mixing] of preparations and/or re-packaging.

Product categories [PC]:

Not available.

Name of contributing environmental scenario and corresponding ERC

ERC2: Formulation of preparations.
Specific Environmental Release Category: ESVOC SpERC 2.2.v1

List of names of contributing worker scenarios and corresponding PROCs

PROC1: Use in closed process, no likelihood of exposure.
PROC2: Use in closed, continuous process with occasional controlled exposure.
PROC3: Use in closed batch process (synthesis or formulation).
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises.
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact).
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).
PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation
. PROC15: Use as laboratory reagent.

Further explanations

Other Process or activity

Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

2.1. Contributing exposure scenario controlling environmental exposure for Formulation of preparations.

Product characteristics

Concentration of the substance in a mixture

Covers percentage substance in the product up to 100 % (unless stated differently).
Substance is complex UVCB. Predominantly hydrophobic.

Physical state

Liquid

Viscosity

Kinematic viscosity

1,6 mm²/s 40 °C

Dynamic viscosity

Not available.

Amounts used

Fraction of EU tonnage used in region:

0,1

Regional use tonnage (tons/year):

5,2 e6

Fraction of Regional tonnage used locally:

0,0058

Annual site tonnage (tons/year):

3 e4

Maximum daily site tonnage (kg/day):

1 e5

Frequency and duration of use

Batch process

Not available.

Continuous process

Emission days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor:

10

Local marine water dilution factor:

100

Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0,01	0,0002	0,0001	

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Treat air emission to provide a typical removal efficiency of (%): 0
Soil	Not available.
Water	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): 86,0. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): 0
Sediment	Not available.
Remarks	Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type	Municipal STP
Discharge rate	2000
Treatment effectiveness	94,7
Sludge treatment technique	Not available.
Measures to limit air emissions	Not available.
Remarks	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d): 2,6e5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	94,7

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment	Not available.
Disposal methods	Not available.
Treatment effectiveness	Not available.
Remarks	External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations	External recovery and recycling of waste should comply with applicable local and/or national regulations.
Treatment effectiveness	Not available.
Remarks	Not available.

Additional good practice advice beyond the REACH CSA Additional information on the basis for the allocation of the indentified OCs and RMMs is contained in the PETRORISK file.

2.2. Contributing exposure scenario controlling worker exposure for Use in closed process, no likelihood of exposure.

Process categories beyond the REACH CSA

Use in closed, continuous process with occasional controlled exposure.
 Use in closed batch process (synthesis or formulation).
 Use in batch and other process (synthesis) where opportunity for exposure arises.
 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact).
 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.
 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.
 Transfer of substance or preparation into small containers (dedicated filling line, including weighing).
 Production of preparations or articles by tableting, compression, extrusion, pelletisation.
 Use as laboratory reagent.

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product Liquid

Vapour pressure Liquid, vapour pressure 0,5 - 10 kPa at STP.

Process temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Amounts used

Not available.

Frequency and duration of use

	Duration	Frequency of use	Remarks
Covers daily exposures up to 8 hours (unless stated differently).	8	1 hours per day	Assumes a good basic standard of occupational hygiene is implemented.

Human factors not influenced by risk management

Exposed skin areas Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Other given operational conditions affecting workers exposure

Area of use	Room size	Temperature	Ventilation rate	Remarks

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Not available.

Technical conditions and measures to control dispersion from source towards the worker Not available.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. wash off any skin contamination immediately. provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

3. Exposure Estimation

Environment

See PETRORISK file in IUCLID Section 13 - "LocalCSR" worksheet.

Health

	Exposure level	RCR	Method	Remarks
General exposures (closed systems)	0,01 ppm	0	**	Inhalation Exposure
General exposures (closed systems)	10 ppm	0.250	**	Inhalation Exposure

General exposures (closed systems)	25 ppm	0.625	**	Inhalation Exposure
General exposures (open systems)	20 ppm	0.500	**	Inhalation Exposure
Process sampling	25 ppm	0.625	**	Inhalation Exposure
Laboratory activities	10 ppm	0.250	**	Inhalation Exposure
Bulk transfers	5 ppm	0.125	**	Inhalation Exposure
Mixing operations (open systems)	50 ppm	0.125	**	Inhalation Exposure
Manual / Transfer from/pouring from containers.	50 ppm	0.125	**	Inhalation Exposure
Drum/batch transfers	50 ppm	0.38	**	Inhalation Exposure
Production of preparations or articles by tableting, compression, extrusion, pelletisation	50 ppm	0.125	**	Inhalation Exposure
Drum and small package filling	50 ppm	0.125	**	Inhalation Exposure
Equipment cleaning and maintenance	50 ppm	0.250	**	Inhalation Exposure
Bulk product storage	10 ppm	0.250	**	Inhalation Exposure

** - The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Health

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.

Available hazard data do not support the need for a DNEL to be established for other health effects. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4 - Exposure Scenario Worker

1. Use as a fuel

List of use descriptors

Sector(s) of Use SU3: Industrial uses.

Product categories [PC]: Not available.

Name of contributing environmental scenario and corresponding ERC ERC7: Industrial use of substances in closed systems.
Specific Environmental Release Category: ESVOC SpERC 7.12a.v1

List of names of contributing worker scenarios and corresponding PROCs
PROC1: Use in closed process, no likelihood of exposure.
PROC2: Use in closed, continuous process with occasional controlled exposure.
PROC3: Use in closed batch process (synthesis or formulation).
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.
PROC16: Using material as fuel sources, limited exposure to unburned product to be expected.

Further explanations

Other Process or activity Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

2.1. Contributing exposure scenario controlling environmental exposure for Industrial use of substances in closed systems.

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).
Substance is complex UVCB. Predominantly hydrophobic.

Physical state Liquid

Viscosity

Kinematic viscosity 1,6 mm²/s 40 °C

Dynamic viscosity Not available.

Amounts used

Fraction of EU tonnage used in region: 0,1

Regional use tonnage (tons/year): 5,5 e5

Fraction of Regional tonnage used locally: 1

Annual site tonnage (tons/year): 5,5 e5

Maximum daily site tonnage (kg/day): 1,8 e6

Frequency and duration of use

Batch process Not available.

Continuous process Emission days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

Type	Emission days (days/year)	Emission factors			Remarks
		Air	Soil	Water	
initial release prior to RMM	300	0,005	0	0,00001	

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Treat air emission to provide a typical removal efficiency of (%): 95

Soil Not available.

Water	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): 84,6. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): 0
Sediment	Not available.
Remarks	Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Organisational measures to prevent/limit release from site	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type	Municipal STP
Discharge rate	2000
Treatment effectiveness	94,7
Sludge treatment technique	Not available.
Measures to limit air emissions	Not available.
Remarks	Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d): 5,3e6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	94,7

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment	Not available.
Disposal methods	Not available.
Treatment effectiveness	Not available.
Remarks	Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations	This substance is consumed during use and no waste of the substance is generated.
Treatment effectiveness	Not available.
Remarks	Not available.

Additional good practice advice beyond the REACH CSA Additional information on the basis for the allocation of the identified OCs and RMMs is contained in the PETRORISK file.

2.2. Contributing exposure scenario controlling worker exposure for Use in closed process, no likelihood of exposure.

Process categories beyond the REACH CSA	Use in closed, continuous process with occasional controlled exposure. Use in closed batch process (synthesis or formulation). Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. Using material as fuel sources, limited exposure to unburned product to be expected.
--	---

Product characteristics

Concentration of the substance in a mixture	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical form of the product	Liquid
Vapour pressure	Liquid, vapour pressure 0,5 - 10 kPa at STP.
Process temperature	Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Amounts used

Not available.

Frequency and duration of use

	Duration	Frequency of use	Remarks
Covers daily exposures up to 8 hours (unless stated differently).	8	1 hours per day	Assumes a good basic standard of occupational hygiene is implemented.

Human factors not influenced by risk management

Exposed skin areas Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Other given operational conditions affecting workers exposure

Area of use	Room size	Temperature	Ventilation rate	Remarks
-------------	-----------	-------------	------------------	---------

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Not available.

Technical conditions and measures to control dispersion from source towards the worker Not available.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. wash off any skin contamination immediately. provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

3. Exposure Estimation**Environment**

See PETRORISK file in IUCLID Section 13 - "LocalCSR" worksheet.

Health

	Exposure level	RCR	Method	Remarks
General exposures (closed systems)	10 ppm	0.250	**	Inhalation Exposure
General exposures (closed systems)	25 ppm	0.625	**	Inhalation Exposure
Transport	5 ppm	0.125	**	Inhalation Exposure
Bulk transfers	50 ppm	0.875	**	Inhalation Exposure
Drum/batch transfers	50 ppm	0.875	**	Inhalation Exposure
Equipment cleaning and maintenance	50 ppm	0.250	**	Inhalation Exposure
Vessel and container cleaning	50 ppm	0.125	**	Inhalation Exposure
Bulk product storage	10 ppm	0.250	**	Inhalation Exposure

** - The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Health

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.

Available hazard data do not support the need for a DNEL to be established for other health effects. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.