

SAFETY DATA SHEET

1. Identification

Product identifier	200P Ethanol	
Other means of identification		
Synonyms	ETHANOL * ETHANOL (ANHYDROUS) * ETHYL ALCOHOL	
Recommended use	Industrial use.	
Recommended restrictions	No other uses are advised.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer/Supplier	Valero Renewable Fuels Company, LLC	
	One Valero Way	
	San Antonio, TX 78269-6000	
General Assistance	210-345-4593	
E-Mail	CorpHSE@valero.com	
Contact Person	Industrial Hygienist	
Emergency Telephone	24 Hour Emergency 866-565-5220	
	1-800-424-9300 (CHEMTREC USA)	

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2A
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger	
Hazard statement	Highly flammable liquid and vapor. Causes serious eye irritation.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection.	
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use alcohol-resistant foam, carbon dioxide or dry powder for extinction.	
Storage	Store in a well-ventilated place. Keep cool.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Substances

_

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	> 99

200P Ethanol

Composition comments	All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.	
4. First-aid measures		
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.	
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.	
Ingestion	Rinse mouth. Get medical attention if symptoms occur.	
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Headache. Coughing.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.	
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.	
5. Fire-fighting measures		
Suitable extinguishing media	Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Water.	
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.	
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.	
General fire hazards	Highly flammable liquid and vapor.	
6. Accidental release meas	sures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.	

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures containment and cleaning up against static discharge. Use only non-sparking tools. Prevent product from entering drains.

> Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

> Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Methods and materials for

Environmental precautions	Ethanol is soluble in water and therefore precautions should be taken to protect surface and groundwater sources from contamination. Stay upwind and away from spill. Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not enter or stay in area unless monitoring indicates that it is safe to do so. Isolate hazard area and restrict entry to emergency crew. Extremely flammable. Review Firefighting Measures, Section 5, before proceeding with clean up. Keep all sources of ignition (flames, smoking, flares, etc.) and hot surfaces away from release. Contain spill in smallest possible area. Recover as much product as possible (e.g. by vacuuming). Stop leak if it can be done without risk. Use water spray to disperse vapors. Use compatible foam to minimize vapor generation as needed. Spilled material may be absorbed by an appropriate absorbent, and then handled in accordance with environmental regulations. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment or drainage systems and natural waterways. Contact fire authorities and appropriate federal, state and local agencies.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3
		1000 ppm
US. ACGIH Threshold Lin	nit Values	
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
US. NIOSH: Pocket Guide	e to Chemical Hazards	
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
logical limit values	No biological exposure limits noted	for the ingredient(s).
propriate engineering htrols	Ventilation rates should be matched exhaust ventilation, or other engined	xhaust ventilation. Good general ventilation should be used. I to conditions. If applicable, use process enclosures, local ering controls to maintain airborne levels below recommende ave not been established, maintain airborne levels to an station and safety shower.
ividual protection measure	es, such as personal protective equip	ment
Eye/face protection	Wear safety glasses with side shield	ds (or goggles).
Skin protection		
Hand protection	Wear appropriate chemical resistan supplier.	t gloves. Suitable gloves can be recommended by the glove
Skin protection		
Other	Wear suitable protective clothing.	
Respiratory protection	limits (where applicable) or to an ac been established), an approved res	ain airborne concentrations below recommended exposure ceptable level (in countries where exposure limits have not pirator must be worn. In the United States of America, if build be instituted to assure compliance with OSHA 29 CFR
		DSH approved respirator with organic vapor/acid gas protecti

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

er i nyelear ana enemiear	
Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Colorless.
Odor	Odorless.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-178.6 °F (-117 °C)
Initial boiling point and boiling range	174.2 °F (79 °C)
Flash point	55.4 °F (13.0 °C) Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	plosive limits
Flammability limit - lower (%)	3.3 % (Ethanol)
Flammability limit - upper (%)	19 % (Ethanol)
Vapor pressure	7.906 kPa (77 °F (25 °C))
Vapor density	1.6
Relative density	0.8
Solubility(ies)	
Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	-0.32
Auto-ignition temperature	685.4 °F (363 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Molecular formula	C2-H6-O
Molecular weight	46.07 g/mol
10. Stability and reactivity	,
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Acids. Alkalis.
Herendeve decembereitien	No becordous decomposition products are known

Hazardous decomposition No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation	High vapor concentrations may cause drowsiness and irritation. Prolonged inhalation may be harmful.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Causes serious eye irritation.

200P Ethanol

No harmful effects expected in amounts likely to be ingested by accident.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Headache. Coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Acute toxicity	Not expect	ed to be acutely toxic.	
Components	Species		Test Results
Ethanol (CAS 64-17-5)			
Acute			
Dermal			
LD50	Rat		> 2000 mg/kg
Inhalation			
Vapor	Mouse		
LC50	Mouse		39 g/m3, 4 Hours
Oral LD50	Rat		7000 - 11000 mg/kg
Skin corrosion/irritation	-	or repeated contact may dry skin ar	id cause irritation.
Serious eye damage/eye irritation	Causes sei	ious eye irritation.	
Respiratory or skin sensitization	on		
Respiratory sensitization	Not a respi	ratory sensitizer.	
Skin sensitization	This produc	ct is not expected to cause skin sen	sitization.
Germ cell mutagenicity		ailable to indicate product or any co or genotoxic.	mponents present at greater than 0.1% are
Carcinogenicity			oup 1 (carcinogenic to humans). Ethanol alone has
NTP Report on Carcinoger Not listed. OSHA Specifically Regular Not listed.		es (29 CFR 1910.1001-1053)	
Reproductive toxicity	Not classifi	ed.	
Specific target organ toxicity - single exposure	Not classifi	ed.	
Specific target organ toxicity - repeated exposure	Not classifi	ed.	
Aspiration hazard	Not an asp	iration hazard.	
Chronic effects			
12. Ecological informatio	on		
Ecotoxicity	Not expected	ed to be harmful to aquatic organism	ns.
Components		Species	Test Results
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Crustacea	LC50	Ceriodaphnia dubia	5012 mg/l, 48 hours
		Daphnia magna	454 mg/l, 11 days
Fish	LC50	Pimephales promelas	13480 mg/l, 96 hours
Chronic			
Crustacea	NOEC	Ceriodaphnia dubia	9.6 mg/l, 10 days

Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	Will not bio-accumulate.	
Partition coefficient n-octar	nol / water (log Kow)	
200P Ethanol (CAS 64-17-5)	-0.32	
Ethanol (CAS 64-17-5)	-0.31	
Mobility in soil	The product is soluble in water.	
Other adverse effects	None expected.	
13. Disposal consideration	ns	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	D001: Waste Flammable material with a flash point <140 °F	

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

 Waste from residues / unused products
 Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

 Contaminated and local regulations are product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN1170
UN proper shipping name	Ethanol
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	П
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	24, IB2, T4, TP1
Packaging exceptions	4b, 150
Packaging non bulk	202
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1170
UN proper shipping name	Ethanol
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	Ш
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1170
UN proper shipping name	ETHANOL
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	

200P Ethanol

Shipping descriptions in this section are offered as examples only. Classification for transport must accurately reflect the material hazards as designated under a variety of regulations and is solely the responsibility of the person offering the material for transport into commerce.

15. Regulatory informatio	n			
US federal regulations	This product is a "Ha Standard, 29 CFR 19	azardous Chemical" as defined by the OSHA Hazard 910.1200.	d Communication	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)				
Not regulated.				
CERCLA Hazardous Su	ubstance List (40 CFR	302.4)		
Not listed. SARA 304 Emergency release notification				
Not regulated.				
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)				
Not listed.				
Toxic Substances Control Act (TSCA)		All components of the mixture on the TSCA 8(b) "active".	inventory are designated	
Superfund Amendments and Re	eauthorization Act of ²	1986 (SARA)		
SARA 302 Extremely hazar	dous substance			
Not listed.				
SARA 311/312 Hazardous chemical	Yes			
Classified hazard categories	Flammable (gases, a Serious eye damage	aerosols, liquids, or solids) e or eye irritation		
SARA 313 (TRI reporting) Not regulated.				
Other federal regulations				
Clean Air Act (CAA) Section	n 112 Hazardous Air P	Pollutants (HAPs) List		
Not regulated.				
Clean Air Act (CAA) Section	n 112(r) Accidental Re	lease Prevention (40 CFR 68.130)		
Not regulated.	Not regulated			
Safe Drinking Water Act (SDWA)	Not regulated.			
		h and Safety in the Flavor Manufacturing Workp	lace	
Ethanol (CAS 64-17	-5)	Low priority		
US state regulations				
US. Massachusetts RTK - S	Substance List			
Ethanol (CAS 64-17-5)				
US. New Jersey Worker and	d Community Right-to	-Know Act		
Ethanol (CAS 64-17-5) US. Pennsylvania Worker a	nd Community Right-	to-Know Law		
Ethanol (CAS 64-17-5) US. Rhode Island RTK				
Ethanol (CAS 64-17-5)				
California Proposition 65				
California Safe Drinking	iny chemicals currently	cement Act of 2016 (Proposition 65): This material listed as carcinogens or reproductive toxins. For ov.		
International Inventories				
Country(s) or region	Inventory name		On inventory (yes/no)*	
Australia	Australian Inventory	of Chemical Substances (AICS)	Yes	
Canada	Domestic Substance	es List (DSL)	Yes	
Canada	Non-Domestic Subst	tances List (NDSL)	No	
China	Inventory of Existing	Chemical Substances in China (IECSC)	Yes	
Europe	European Inventory	of Existing Commercial Chemical	Yes	

200P Ethanol

Substances (EINECS)

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	18-December-2014		
Revision date	15-December-2020		
Version #	02		
NFPA ratings	2 0		
References	ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices EPA: AQUIRE database NLM: Hazardous Substances Data Base HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens		
Disclaimer	The information in this Safety Data Sheet (SDS) was obtained from sources believed to be reliable and accurate, and is not represented as being absolutely complete. The end user of this product has the responsibility for evaluating the adequacy of the data for the intended application and conditions of use; for determining the safety, toxicity, regulatory requirements, and suitability of the product under these conditions; and for obtaining additional or clarifying data where uncertainty exists. The data serves as general guidance only, and is to be used in combination with professional judgement of persons experienced in a specific application, use or process; and additional data may be required. Valero Marketing & Supply Co., (Valero) provides this data without any warranty, expressed or implied regarding its correctness or accuracy; and does not assume any liability arising out of product handling, storage, use or disposal by others.		