VALERO

SAFETY DATA SHEET

1. Identification

Product identifier Green Diesel R100 Renewable Diesel

Other means of identification

SDS number R100-V-GHS

Synonyms Green Diesel, Renewable Diesel, R99, R100 See section 16 for complete information.

Recommended use This product is intended for use as a refinery feedstock, fuel or for use in engineered processes.

Use in other applications may result in higher exposures and require additional controls, such as

local exhaust ventilation and personal protective equipment.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier Valero Marketing & Supply Company and Affiliates

One Valero Way

San Antonio, TX 78269-6000

General Assistance 210-345-4593

E-Mail CorpHSE@valero.com
Contact Person Industrial Hygienist

Emergency Telephone 24 Hour Emergency 866-565-5220

1-800-424-9300 (CHEMTREC USA)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsAcute toxicity, inhalationCategory 4Skin corrosion/irritationCategory 2CarcinogenicityCategory 2

Specific target organ toxicity, repeated

exposure

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Suspected of causing

cancer. May cause damage to organs (blood, thymus, liver) through prolonged or repeated

Category 2 (blood, thymus, liver)

Category 2

exposure. May be fatal if swallowed and enters airways.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not breathe mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area.

Green Diesel R100 Renewable Diesel

915271 Version #: 01 Revison date: 28-May-2014 Print date: 28-May-2014 1 / 8

If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and Response

keep comfortable for breathing. If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower. If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Take off contaminated clothing and wash before reuse. In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction. Do

NOT induce vomiting.

Storage Store locked up. Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Fuels, diesel, C9-18-alkane branched and linear	1159170-26-9	100

4. First-aid measures

Inhalation If symptomatic, move to fresh air. If breathing is difficult, give oxygen. Get medical attention if

symptoms persist.

Skin contact Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes. Remove contaminated clothing and shoes. Get medical attention. Wash contaminated

clothing before reuse. Destroy or thoroughly clean contaminated shoes.

Eye contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses.

Remove contact lenses, if present and easy to do. Get medical attention.

In case of irritation from airborne exposure, move to fresh air. Get medical attention if symptoms

persist.

Call a physician or poison control center immediately. DO NOT induce vomiting. If victim is fully Ingestion

conscious, give a cupful of water. Never give anything by mouth to an unconscious person. If

vomiting occurs, keep head lower than the hips to help prevent aspiration.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Irritation of nose and throat. Irritation of eyes and mucous membranes. Skin irritation. Liver enlargement. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

In case of shortness of breath, give oxygen. Symptoms may be delayed. Keep victim under observation. Treat symptomatically. The toxicological properties of this material have not been fully investigated.

If exposed or concerned: get medical attention/advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions Water. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use a solid water stream as it may scatter and spread fire.

Vapor may cause flash fire. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge. The product can accumulate electrostatic charges, which may cause an electrical spark (ignition source).

Wear full protective clothing, including helmet, self-contained positive pressure or pressure

demand breathing apparatus, protective clothing and face mask.

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. In the event of fire, cool tanks with water spray. Cool containers exposed to flames with water until well after the fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Vapors may form explosive air mixtures even at room temperature. Prevent buildup of vapors or gases to explosive concentrations. Do not move cargo or vehicle if cargo has been exposed to heat. Water runoff can cause environmental damage. Use compatible foam to minimize vapor generation as

Specific methods Use water spray to cool unopened containers. Prevent build-up of vapors or gasses to explosive concentrations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up Keep unnecessary personnel away. Local authorities should be advised if significant spills cannot be contained. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the SDS for Personal Protective Equipment.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Extinguish all flames in the vicinity. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Small Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Cover with plastic sheet to prevent spreading. Collect spillage. Following product recovery, flush area with water. Prevent product from entering drains. Do not allow material to contaminate ground water system. Clean surface thoroughly to remove residual contamination. Wipe up with absorbent material (e.g. cloth, fleece).

Never return spills in original containers for re-use.

Environmental precautions

If facility or operation has an "oil or hazardous substance contingency plan", activate its procedures. Stay upwind and away from spill. Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not enter or stay in area unless monitoring indicates that it is safe to do so. Isolate hazard area and restrict entry to emergency crew. Flammable. Review Firefighting Measures, Section 5, before proceeding with clean up. Keep all sources of ignition (flames, smoking, flares, etc.) and hot surfaces away from release. Contain spill in smallest possible area. Recover as much product as possible (e.g. by vacuuming). Stop leak if it can be done without risk. Use water spray to disperse vapors. Spilled material may be absorbed by an appropriate absorbent, and then handled in accordance with environmental regulations. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment or drainage systems and natural waterways. Contact fire authorities and appropriate federal, state and local agencies. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, contact the National Response Center at 1-800-424-8802. For highway or railways spills, contact Chemtrec at 1-800-424-9300.

7. Handling and storage

Precautions for safe handling

Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.

Wear personal protective equipment. Do not breathe gas/fumes/vapor/spray. Avoid contact with eves, skin, and clothing. Do not taste or swallow, Avoid prolonged exposure. Use only with adequate ventilation. Wash thoroughly after handling. The product is extremely flammable, and explosive vapor/air mixtures may be formed even at normal room temperatures. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. When using, do not eat, drink or smoke. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities Flammable liquid storage. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. The pressure in sealed containers can increase under the influence of heat. Keep container tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits

No exposure limits noted for ingredient(s).

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses. If splash potential exists, wear full face shield or chemical goggles.

Skin protection

Hand protection

Avoid exposure - obtain special instructions before use. Wear protective gloves. Protective gloves.

Other

Wear chemical-resistant, impervious gloves. Full body suit and boots are recommended when handling large volumes or in emergency situations. Flame retardant protective clothing is recommended.

Green Diesel R100 Renewable Diesel

Revison date: 28-May-2014 Print date: 28-May-2014 915271 Version #: 01

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workplace exposure limits for product or components are exceeded, NIOSH approved equipment should be worn. Proper respirator selection should be determined by adequately trained personnel, based on the contaminants, the degree of potential exposure and published respiratory protection factors. This equipment should be available for nonroutine and emergency

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Consult supervisor for special handling instructions. Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Wash hands before breaks and immediately after handling the product. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance Colorless liquid.

Physical stateLiquid.FormLiquid.ColorColorless.

Odorless to mild paraffin.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

Flash point

354.2 - 588.2 °F (179 - 309 °C)

132.8 - 136.4 °F (56.0 - 58.0 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature494.6 °F (257 °C)Decomposition temperatureNot available.Viscosity1.9 - 4.1 cP (40°C)

Other information

Density 0.77 g/ml (15°C)

10. Stability and reactivity

Reactivity Not available.

Chemical stability Stable under normal temperature conditions and recommended use.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Ignition sources. Contact with incompatible materials. Do not pressurize,

cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static

electricity, or other sources of ignition; they may explode and cause injury or death.

Incompatible materials Strong oxidizing agents. Reducing agents. Acids. Alkalis.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion May cause lung damage if swallowed.

InhalationHarmful if inhaled.Skin contactCauses skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of nose and throat. Irritation of eyes and mucous membranes. Skin irritation. Liver enlargement. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause damage to organs through prolonged or

repeated exposure.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful: may cause lung damage if swallowed.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not a skin sensitizer.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity International Agency for Research on Cancer (IARC): Whole diesel engine exhaust – IARC Group

1. Exposure may cause lung cancer and also noted a positive association with an increased risk

of bladder cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (blood, thymus, liver) through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Further information Symptoms may be delayed.

12. Ecological information

EcotoxicityToxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability
Bioaccumulative potential
Mobility in soil
Other adverse effects
Not available.
Not available.

13. Disposal considerations

Disposal instructions Dispose in accordance with all applicable regulations. This material and its container must be

disposed of as hazardous waste. Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate

ponds, waterways or ditches with chemical or used container.

Hazardous waste code D001: Waste Flammable material with a flash point <140 °F

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

UN number UN1202 UN proper shipping name Diesel fuel

Green Diesel R100 Renewable Diesel

915271 Version #: 01 Revison date: 28-May-2014 Print date: 28-May-2014 5 / 8

Transport hazard class(es)

Combustible Liquid **Class**

Subsidiary risk Packing group Ш

Environmental hazards

Marine pollutant Yes

Special precautions for user Not available.

Special provisions 144, B1, IB3, T2, TP1

150 Packaging exceptions Packaging non bulk 203 Packaging bulk 242

IATA

UN1202 **UN** number **UN** proper shipping name Gas oil

Transport hazard class(es) Class 3 Subsidiary risk Ш Packing group **Environmental hazards** Yes **ERG Code** 31

Special precautions for user Not available.

IMDG

UN1202 **UN** number **UN** proper shipping name **DIESEL FUEL**

Transport hazard class(es) Class Subsidiary risk

Ш Packing group

Environmental hazards

Marine pollutant F-E, S-E **EmS** Special precautions for user Not available. Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is hazardous according to OSHA 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

3

Yes

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No **Hazard categories**

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Green Diesel R100 Renewable Diesel

915271 Version #: 01 Revison date: 28-May-2014 Print date: 28-May-2014

Prepared by 3E Company

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulationsThis product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Inventory name

Not listed.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 28-May-2014

Revision date - Version # 01

United States & Puerto Rico

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA Ratings



Green Diesel R100 Renewable Diesel

915271 Version #: 01 Revison date: 28-May-2014 Print date: 28-May-2014

7/8

Yes

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

References

EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

This material Safety Data Sheet (SDS) was prepared in accordance with 29 CFR 1910.1200 by Valero Marketing & Supply Co., ("VALERO"). VALERO does not assume any liability arising out of product use by others. The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.