

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name or designation of the mixture	Kerosene - All Grades (Refer to Synonyms for Product Name)
Registration number	-
Synonyms	Kerosene, Unmarked * Kerosene, Marked
SDS number	2009
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	Use as a fuel.
Uses advised against	All other uses.
1.3. Details of the supplier of th	e safety data sheet
Supplier	
Company name	Valero Energy (Ireland) Ltd
	1st Floor, Block B
Address	D22 X0Y3, Quarryvale
	Ireland
Telephone	01/210 345 4593 (General information; US)
e-mail	CorpHSE@valero.com
Contact person	Industrial Hygienist
1.4. Emergency telephone number	0044/(0)18 65 407333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
Health hazards Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Specific target organ toxicity - single	Category 2 Category 3 narcotic effects	H336 - May cause drowsiness or
exposure	Category 5 harcolic cheels	dizziness.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.
Environmental hazards		
Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.

2.2. Label elements

Contains:

Label according to Regulation (EC) No. 1272/2008 as amended

Kerosine (petroleum), hydrodesulphurized, Kerosine (petroleum), sweetened

Hazard pictograms



Signal word Hazard statements

H226

Flammable liquid and vapour.

H304 H315 H336 H411	May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	
P210 P261 P273 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapours. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	
P301 + P310 P331	IF SWALLOWED: Immediately call a POISON CENTRE/doctor. Do NOT induce vomiting.
Storage	Not assigned.
Disposal	Not assigned.
Supplemental information on the label	None.
2.3. Other hazards	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight. The mixture does not contain any substances having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General	information
General	mormation

% CAS-No. / EC No. REACH Registration No. Index No. Notes		
% CAS-No. / EC No. REACH Registration No. Index No. Notes 0 - 100 64742-81-0 01-2119462828-25 649-423-00-8 265-184-9		
ssification: Flam. Liq. 3;H226, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411		
etened 0 - 100 91770-15-9 01-2119502385-46-0021 649-427-00-X 294-799-5		
ssification: Flam. Liq. 3;H226, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411		
All concentrations are in percent by weight unless ingredient is a gas. The full text for all H-statements is displayed in section 16.		
easures		
Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.		
easures		
Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.		
Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.		
Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.		
Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.		
Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness Headache. Nausea, vomiting. Diarrhoea. Direct contact with eyes may cause temporary irritation Skin irritation. May cause redness and pain.		
Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.		

SECTION 5: Firefighting measures

Flammable liquid and vapour.

5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Before entering storage tanks and commencing any operation in a confined area check the atmosphere for oxygen content and flammability. (Subject to applicability) If sulphur compounds are suspected to be present in the product, check the atmosphere for H2S content. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).
7.3. Specific end use(s)	Use as a Fuel. For detailed information, see section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits	No exposure limits noted for ingredient(s).
Biological limit values	No biological exposure limits noted for the ingredient(s).
Recommended monitoring procedures	Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Derived no effect levels (DNEL	.s)			
General population				
Components		Value	Assessment factor	Notes
Kerosine (petroleum), hydro	desulphurized (CAS 64742-81-0)		
Long-term, Systemic, C	Iral	18.75 mg/kg bw/day	40	Repeated dose toxicity
Kerosine (petroleum), swee	tened (CAS 917	70-15-9)		
Long-term, Systemic, C	Dral	18.75 mg/kg bw/day	40	Repeated dose toxicity
Predicted no effect concentrations (PNECs)	Not available	e.		
8.2. Exposure controls				
Appropriate engineering controls	Ventilation ra exhaust ven exposure lin	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
Individual protection measure	· ·			
General information		Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.		
Eye/face protection		Chemical respirator with organic vapour cartridge and full facepiece. Eye protection should meet standard EN 166.		
Skin protection				
- Hand protection	thickness: 0	Wear suitable gloves tested to EN374. In full contact: Glove material: Nitrile rubber. Layer thickness: 0.225 mm. Breakthrough time: >480 min. Splash contact: Glove material: Neoprene; Layer thickness: 0.75 mm; Breakthrough time: 10-30 min.		
- Other	Wear appro	Wear appropriate chemical resistant clothing.		
Respiratory protection		In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P2) can be used.		
Thermal hazards	Wear appro	oriate thermal protective clot	hing, when necessary.	
Hygiene measures	after handlin	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
Environmental exposure controls	with the requencies engineering	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.		

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	Not determined.
Odour	Not determined.
Melting point/freezing point	-49 °C (-56.2 °F)
Boiling point or initial boiling point and boiling range	146 - 299 °C (294.8 - 570.2 °F)
Flammability	Flammable liquid and vapour.
Upper/lower flammability or expl	osive limits
Explosive limit - lower (%)	Not determined.
Explosive limit – upper (%)	Not determined.
Flash point	29 - 70 °C (84.2 - 158 °F)
Auto-ignition temperature	220 - 250 °C (428 - 482 °F)
Decomposition temperature	Not determined.
рН	Not determined.
Kinematic viscosity	Not determined.
Solubility	
Solubility (water)	Insoluble in water.
Partition coefficient (n-octanol/water) (log value)	Not determined.

Vapour pressure	0.06 kPa (20 °C (68 °F))		
Density and/or relative density Relative density	Not determined.		
Vapour density	4.5		
Particle characteristics	Not applicable.		
9.2. Other information			
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.		
9.2.2. Other safety characteristic	CS		
Specific gravity	0.8		
Viscosity	1 - 2.4 cSt (40 °C (104 °F))		
SECTION 10: Stability and	l reactivity		
10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.		
10.2. Chemical stability	Material is stable under normal conditions.		
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions	of normal use.	
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.		
10.5. Incompatible materials	Strong oxidising agents.		
10.6. Hazardous decomposition products	No hazardous decomposition products are know	vn.	
SECTION 11: Toxicologica	al information		
General information	Occupational exposure to the substance or mixi	ture may cause adverse effects.	
Information on likely routes of e	exposure		
Inhalation	May cause drowsiness and dizziness. Headach harmful.	e. Nausea, vomiting. Prolonged inhalation may be	
Skin contact	Causes skin irritation.		
Eye contact	Direct contact with eyes may cause temporary i	rritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.		
Symptoms	Aspiration may cause pulmonary oedema and p Headache. Nausea, vomiting. Diarrhoea. Skin ir	oneumonitis. May cause drowsiness and dizziness. ritation. May cause redness and pain.	
11.1. Information on hazard clas	sses as defined in Regulation (EC) No 1272/200	8	
Acute toxicity	May be fatal if swallowed and enters airways.		
Components	Species	Test Results	
Kerosine (petroleum), hydrodesul	ohurized (CAS 64742-81-0)		
Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Inhalation			
Vapour			
LC50	Rat	> 5.28 mg/l, 4 Hours	
Oral			
Oral LD50	Rat	> 5.28 mg/l, 4 Hours > 5000 mg/kg	
Oral	Rat		
Oral LD50 Kerosine (petroleum), sweetened	Rat		
Oral LD50 Kerosine (petroleum), sweetened <u>Acute</u>	Rat		
Oral LD50 Kerosine (petroleum), sweetened <u>Acute</u> Dermal	Rat (CAS 91770-15-9)	> 5000 mg/kg	
Oral LD50 Kerosine (petroleum), sweetened <u>Acute</u> Dermal LD50 Inhalation Vapour	Rat (CAS 91770-15-9) Rabbit	> 5000 mg/kg > 2000 mg/kg	
Oral LD50 Kerosine (petroleum), sweetened Acute Dermal LD50 Inhalation Vapour LC50	Rat (CAS 91770-15-9)	> 5000 mg/kg	
Oral LD50 Kerosine (petroleum), sweetened Acute Dermal LD50 Inhalation Vapour LC50 Oral	Rat (CAS 91770-15-9) Rabbit Rat	> 5000 mg/kg > 2000 mg/kg > 5.28 mg/l, 4 Hours	
Oral LD50 Kerosine (petroleum), sweetened Acute Dermal LD50 Inhalation Vapour LC50	Rat (CAS 91770-15-9) Rabbit	> 5000 mg/kg > 2000 mg/kg	

Serious eye damage/eye irritation	Direct conta	act with eyes may cause temporar	y irritation.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.			
Skin sensitisation	Based on available data, the classification criteria are not met.			
Germ cell mutagenicity	Based on available data, the classification criteria are not met.			
Carcinogenicity	Based on available data, the classification criteria are not met.			
Reproductive toxicity	Based on a	vailable data, the classification cri	teria are not met.	
Specific target organ toxicity - single exposure	May cause	drowsiness and dizziness.		
Specific target organ toxicity - repeated exposure	Based on a	vailable data, the classification cri	teria are not met.	
Aspiration hazard	May be fata	May be fatal if swallowed and enters airways.		
Mixture versus substance information	No informa	No information available.		
11.2. Information on other hazar	rds			
Endocrine disrupting properties	to human h 1907/2006,	This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.		
Other information	May be abs	sorbed through the skin.		
SECTION 12: Ecological in	nformation	ı		
12.1. Toxicity		Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.		
Components		Species	Test Results	
Kerosine (petroleum), hydrodesul µ Aquatic Acute	ohurized (CAS	S 64742-81-0)		
Crustacea	EL50	Daphnia	1.4 mg/l, 48 hours	
Fish	LL50	Freshwater fish	> 2 - < 5 mg/l, 96 hours	
Chronic				
Fish	NOEL	Freshwater fish	0.098 mg/l	
Kerosine (petroleum), sweetened Aquatic <i>Acut</i> e	(CAS 91770-	15-9)		
Crustacea	EL50	Daphnia	1.4 mg/l, 48 hours	
Fish	LL50	Freshwater fish	> 2 - < 5 mg/l, 96 hours	
Chronic				
Fish	NOEL	Freshwater fish	0.098 mg/l	
12.2. Persistence and degradability	Expected to	be inherently biodegradable.		
12.3. Bioaccumulative potential	The produc	t is not bioaccumulating.		
Partition coefficient n-octanol/water (log Kow)	Not availab	le.		
Bioconcentration factor (BCF)	Not availab	le.		
12.4. Mobility in soil	No data ava	ailable.		
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.			
12.6. Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.			
12.7. Other adverse effects	Oil spills ar	e generally hazardous to the envir	ronment.	
SECTION 13: Disposal co	nsideratio	ns		

SECTION 13: Disposal consideratio

13.1. Waste treatment methods Residual waste

Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	13 07 03* The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

2E	CTION 14: Transport Inf	ormation
AD	R	
	14.1. UN number	UN1223
	14.2. UN proper shipping	KEROSENE
	name	
	14.3. Transport hazard class	(es)
	Class	3
	Subsidiary risk	-
	Label(s)	3
	Hazard No. (ADR)	30
	Tunnel restriction code	
	14.4. Packing group	
	14.5. Environmental hazards	Yes
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	, , , , , , , , , , , , , , , , , , , ,
RID		
	14.1. UN number	UN1223
	14.2. UN proper shipping	KEROSENE
	name	
	14.3. Transport hazard class	les)
	Class	3
	Subsidiary risk	-
	Label(s)	3
	14.4. Packing group	III
	14.5. Environmental hazards	Yes
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
AD	N	
	14.1. UN number	UN1223
	14.2. UN proper shipping	Kerosene
	name	
	14.3. Transport hazard class((es)
	Class	3
	Subsidiary risk	-
	Label(s)	3
	14.4. Packing group	111
	14.5. Environmental hazards	
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
ΙΑΤ		
	14.1. UN number	UN1223
	14.2. UN proper shipping	Kerosene
	name	
	14.3. Transport hazard class	
	Class	3
	Subsidiary risk	
	Label(s)	3
	14.4. Packing group	
	14.5. Environmental hazards	
	ERG Code	3L
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
1845	for user	
IME		

IMDG

14.1. UN number UN1223

14.2. UN proper shipping name	KEROSENE		
14.3. Transport hazard class(es)			
Class	3		
Subsidiary risk	-		
Label(s)	3		
14.4. Packing group			
14.5. Environmental hazards	6		
Marine pollutant	Yes		
EmS	F-E, S-E		
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.		
14.7. Maritime transport in bulk according to IMO instruments	Not established.		
General information	Shipping descriptions in this section are offered as examples only. Classification for transport must accurately reflect the material hazards as designated under a variety of regulations and is solely the responsibility of the person offering the material for transport into commerce.		
SECTION 15: Regulatory information			

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Kerosine (petroleum), hydrodesulphurized 3 (CAS 64742-81-0)

Kerosine (petroleum), sweetened (CAS 91770-15-9)

3 Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended Not listed.

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex II, as amended Not listed

Other EU regulations Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS

- E2 Hazardous to the Aquatic Environment Chronic

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.	
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.	
15.2. Chemical safety assessment	Chemical Safety Assessment has been carried out.	
SECTION 16: Other information		
List of abbreviations		

List of abbreviations	
	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstract Service. CEN: European Committee for Standardization. IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent, bioaccumulative and toxic. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TWA: Time Weighted Average. vPvB: Very persistent and very bioaccumulative.
References	Chemical safety report. CONCAWE ECHA: European Chemical Agency.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements, which are not written out in full	
under sections 2 to 15	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Training information	Follow training instructions when handling this material.
Disclaimer	The information in this Safety Data Sheet (SDS) was obtained from sources believed to be reliable and accurate, and is not represented as being absolutely complete. The end user of this product has the responsibility for evaluating the adequacy of the data for the intended application and conditions of use; for determining the safety, toxicity, regulatory requirements, and suitability of the product under these conditions; and for obtaining additional or clarifying data where uncertainty exists. The data serves as general guidance only, and is to be used in combination with professional judgement of persons experienced in a specific application, use or process; and additional data may be required.